|                           | CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING<br>CONNECTING | osition Dee<br>PC, Bannockt<br>n-American co | c <b>laration</b><br>ourn, Illinois. A<br>opyright conve | All rights reserved u ntions. | nder both  | This docume<br>level parts, t | ent is a declarat          | tion of<br>encom               | the substances<br>passes all low | within the<br>er level mat | manufactur<br>erials for wl     | er listed it<br>hich the m | em. Note: i<br>anufacture | if the item is an as<br>r has engineering | ssembly with lowe<br>responsibility. |
|---------------------------|--|--|--|-------------------------------|--|-------------------------------|----------------------------|--------------------------------|----------------------------------|----------------------------|---------------------------------|----------------------------|---------------------------|---|--------------------------------------|
| 1752-21.1                 | IPC Web Site for Information on IPC-1752 Standard Form Type<br>http://www.ipc.org/IPC-175x Distribute  |  |  |                               | * Declaration Class *<br>Class 6 - RoHS Yes/No, Homogeneous Materi |                               |                            |                                |                                  | als and Mfg Information    |                                 |                            |                           |   |                                      |
| Supplie                   | r Information  |  |  |                               |  |                               |                            |                                |                                  |                            |                                 |                            |                           |   |                                      |
| Company name* Com         |  |  |  | Company unique ID             |  |                               | Unique ID Authority        |                                |                                  |                            |                                 | Response Date*             |                           |   |                                      |
| onsemi                    |  |  |  |                               |  |                               |                            |                                |                                  |                            |                                 | 2024-05-09                 |                           |   |                                      |
| Contact N                 | lame   |  | Title - Contact  |                               |  | ]                             | Phone - Contact*           |                                |                                  |                            |                                 | Email - Contact*           |                           |   |                                      |
| Product-l                 | Env-Stewards   |  | Product Enviro Compliance                                |                               |  |                               | NA                         |                                |                                  |                            | Product-Env-Stewards@onsemi.com |                            |                           |   |                                      |
| uthorize                  | ed Representative*   |  | Title - Representative                                   |                               |  | ]                             | Phone - Representative*    |                                |                                  |                            | Email - Representative*         |                            |                           |   |                                      |
| Product-l                 | Env-Stewards   |  | Product Enviro Compliance                                |                               |  |                               | NA                         |                                |                                  |                            | Product-Env-Stewards@onsemi.com |                            |                           |   |                                      |
|                           | Requester Item Number   Mfr Item     1N5925B   |  | Number Mfr Item Name                                     |                               |  |                               | Effective Date             | ate Version Manufacturing Site |                                  | ring Site                  | 1                               | Weight*                    | UOM                       | Unit Type                                 |                                      |
|                           |  |  | BRLG   | RLG ZEN SUR30 REG 3W 10V      |  |                               | 2024-05-09 CNP             |                                |                                  | 361.01                     |                                 | mg                         | Each                      |   |                                      |
| /Ianufa                   | cturing Proccess Information   | tion   |  |                               |  |                               |                            |                                |                                  |                            |                                 |                            |                           | L   |                                      |
|                           | Terminal Plating / Grid Array Material   |  | Ferminal Base Alloy J-STD-020                            |                               | -STD-020 MSI   | L Rating                      | Peak Process Body Temperat |                                | ure Max Time at Peak Temp        |                            | Temperat                        | ure Numb                   | per of Reflow Cyc         | cles                                      |                                      |
| Matte Tin (Sn) - annealed |  | CU Alloy NA                                  |  |                               | 0 C  |                               | С                          | 30                             |                                  | secon                      | ds 3                            |                            |                           |   |                                      |
| omments                   | 8  |  |  |                               |  |                               |                            |                                |                                  |                            |                                 |                            |                           |   |                                      |
|                           |  |  |  |                               |  |                               |                            |                                |                                  |                            |                                 |                            |                           |   |                                      |
| or more                   | information regarding material   | composition                                  | please refer to  | page 3                        |  |                               |                            |                                |                                  |                            |                                 |                            |                           |   |                                      |

| RoHS Material Composition Declaration  |   |  |   | Declaration Type *  | Detailed  |  |  |  |  |  |  |
|--|---|--|---|---|---|--|--|--|--|--|--|
| Directive 2015/863/EU amending RoHS<br>Directive 2011/65/EU  | RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP). |  |   |   |   |  |  |  |  |  |  |
| cadmium, hexavalentchromium, polybromina<br>contains a RoHS restricted substance inexces<br>encompass all such components. Supplier cer<br>as of the date that Supplier completes this for<br>Company acknowledges that Supplier may h<br>independently verified information provided<br>certification in this paragraph. If the Company | ated biphenyls and/or polybrominated dip<br>s of an applicable quantity limit, please in<br>iffies that it gathered the information it pr<br>m.Supplier acknowledges that Company<br>ave relied on informationprovided by oth<br>by others, Supplier agrees that, at a minir<br>and the Supplier enter into a written agr<br>esource of the Supplier's liability and the  | henyl ethers (each a "RoHS restricted substa<br>ndicate below which, if any, RoHS exemption<br>ovides in this form using appropriate methoo<br>will rely on this certification in determining<br>ers in completing this form, and that Supplie<br>num, itssuppliers have provided certification<br>eement with respect to the identified part, the<br>Company's remedies for issues that arise reg | nce") in exco<br>n you believe<br>ls to ensure i<br>the compliar<br>r may not ha<br>s regarding t<br>terms and co | e may apply. If the part is an assembly with low<br>s accuracy and that such information is true an<br>ce of its products with European Union member<br>de independently verified such information. Ho<br>neir contributions to the part, and those certifica | ove. If a homogeneous material within the part<br>er level components, the declaration shall<br>d correct to the best of its knowledge and belief,<br>er state laws that implement the RoHS Directive.<br>wever, in situations where Supplier has not<br>ations are at least as comprehensive as the<br>anty rights and/or remedies provided as part of |  |  |  |  |  |  |
| RoHS Declaration * 4 - Item(   | s) does not contain RoHS restricted subst   | ances per the definition above except for sele   | ected exempt  | ions Supplier Acceptance  | * Accepted  |  |  |  |  |  |  |
| Exemption: 7a: Lead in high melting temp   | erature type solders (i.e. lead based sol   | der alloys containing 85% by weight or m   | ore lead).  |   |   |  |  |  |  |  |  |
| Exemption List Version   | EL-2011/534/EU  |  |   |   |   |  |  |  |  |  |  |
| Declaration Signature  |   |  |   |   |   |  |  |  |  |  |  |
| Instructions: Complete all of the required<br>Requester) and click on Submit Form to h   |   |  | e drop-dowi   | a. This will display the signature area. Digita   | lly sign the declaration (if required by the  |  |  |  |  |  |  |
| Supplier Digital Signature   | astislav Drska  | Le   |   |   |   |  |  |  |  |  |  |

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3

| Homogeneous Material | Weight | Unit of Measure | Level    | Substance                  | CAS              | Exempt | Weight  | Unit of Measure |
|----------------------|--------|-----------------|----------|----------------------------|------------------|--------|---------|-----------------|
| Die                  | 2.67   | mg              | Supplier | Silicon (Si)               | 7440-21-3        |        | 2.67    | mg              |
| Die Attach Solder    | 12.67  | mg              | Supplier | Silver (Ag)                | 7440-22-4        |        | 0.3168  | mg              |
|                      |        |                 | А        | Lead (Pb)                  | 7439-92-1        | 7a     | 11.7198 | mg              |
|                      |        |                 | Supplier | Tin (Sn)                   | 7440-31-5        |        | 0.6335  | mg              |
| Lead Frame           | 198.45 | mg              | В        | Nickel (Ni)                | 7440-02-0        |        | 2.183   | mg              |
|                      |        |                 | Supplier | Copper (Cu)                | 7440-50-8        |        | 196.267 | mg              |
| Mold Compound-Black  | 139.28 | mg              |          | Metal Hydroxide            | proprietary data |        | 6.964   | mg              |
|                      |        |                 | Supplier | Carbon Black (C)           | 1333-86-4        |        | 1.3928  | mg              |
|                      |        |                 | Supplier | Fused Silica (SiO2)        | 60676-86-0       |        | 104.46  | mg              |
|                      |        |                 | Supplier | Ortho-Cresol Novolac Resin | 29690-82-2       |        | 13.928  | mg              |
|                      |        |                 | Supplier | Phenolic Resin (Novolac)   | 9003-35-4        |        | 12.5352 | mg              |
| Plating              | 7.94   | mg              | Supplier | Tin (Sn)                   | 7440-31-5        |        | 7.94    | mg              |