ABSOCIATION CONNECTING ELECTRONICS INDUSTRIES® INCLUSTRES	IPC. Bannockl	ourn. Illinois. A	Il rights reserved untions.	under both	This docume level parts, t	ent is a declarat	ion of the stencompasse	ubstances s all lowe	within the ma r level materia	nufacturer li ls for which	isted item. Note: the manufactur	if the item is an a er has engineering	ssembly with lowe responsibility.	
	-21.1 IPC Web Site for Information on IPC-1752 Standard Form Distribution Distribut				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Info					and Mfg Inform	ation			
Supplier Information														
Company name*		Company unique ID				Unique ID Authority					Response Date*			
semi										20	2024-05-17			
Title - Contact				Phone - Contact*					En	Email - Contact*				
Product-Env-Stewards Product Envi			nviro Compliance			NA				Pi	Product-Env-Stewards@onsemi.com			
Authorized Representative* Title - Represe			sentative			Phone - Representative*			En	Email - Representative*				
Product-Env-Stewards Product Enviro C			o Compliance		NA			P	Product-Env-Stewards@onsemi.com					
Requester Item Number	Mfr Iten	n Number	Mfr Item Name			Effective Date	Version	1	Manufacturing Site		Weight*	UOM	Unit Type	
	CAT240	CAT24C08C4ATR 8KB I2C		KB I2C SER EEPROM		2024-05-17		(CNQ		0.4682	mg	Each	
Manufacturing Proccess Informa	ition													
Terminal Plating / Grid Array M	nal Plating / Grid Array Material Terminal Base		Alloy	J-STD-020 MSL Rating		Peak Process Body Temperature M		e Max Time	at Peak Ten	ak Temperature Number of Reflow Cycles		cles		
SnAgCu CU Alloy		CU Alloy		1		260		С	30		seconds 3			
Comments														
evel 1 - maximum time at peak temperat	ure during so	ldering is 10-3	0 seconds											
or more information regarding materia	composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted						
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all						
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	stislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.3895	mg	Supplier	Silicon (Si)	7440-21-3		0.3895	mg
Protection coat	0.0105	mg		Polyimide	proprietary data		0.0105	mg
RDL Sputter	4.0E-4	mg	Supplier	Titanium (Ti)	7440-32-6		0.0001	mg
			Supplier	Copper (Cu)	7440-50-8		0.0003	mg
Solder Ball	0.0523	mg	Supplier	Silver (Ag)	7440-22-4		0.0014	mg
			Supplier	Tin (Sn)	7440-31-5		0.0506	mg
			Supplier	Copper (Cu)	7440-50-8		0.0003	mg
JBM/RDL PCu	0.0153	mg	Supplier	Copper (Cu)	7440-50-8		0.0153	mg
UBM Sputter	2.0E-4	mg	Supplier	Titanium (Ti)	7440-32-6		0	mg
			Supplier	Copper (Cu)	7440-50-8		0.0002	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).