| | | | IPC-1752 Stand | dard | Form Type * | | | | | | | | | | |
|----------------------|-----------------------------|---------------------------|-------------------------------|--|--------------|-------------------------|---------------------|---|---------------------------------|---------------------------------|------|--------------------------|--|--|--|
| | nformation | | | IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute | | | | | | | | ials and Mfg Information | | | |
| ompany nan | | | | | | | | | | | | | | | |
| | Company name* | | | Company unique ID | | | Unique ID Authority | | | Response Date* | | | | | |
| semi | | | | | | | | | 2024-05-16 | | | | | | |
| ontact Name | e | Title - Conta | Title - Contact | | | Phone - Contact* | | | Email - Contact* | | | | | | |
| roduct-Env | -Stewards | Product Enviro Compliance | | | | NA | | | Product-Env-Stewards@onsemi.com | | | | | | |
| uthorized R | epresentative* | Title - Representative | | | I | Phone - Representative* | | | Email - Representative* | | | | | | |
| Product-Env-Stewards | | | Product Enviro Compliance | | | | NA | | | Product-Env-Stewards@onsemi.com | | | | | |
| Re | Requester Item Number | | Mfr Item Number Mfr Item Name | | | Ei | | Version | Manufacturing Site | Weight* | UOM | Unit Type | | | |
| | | EGP10K HER DO41 GPP | | HER DO41 GPPN | 1 1A 800V | | 2024-05-16 TSCBE | | 339.995 | mg | Each | | | | |
| | uring Process Informa | | | | amp 020 144 | | | D 1 m | | | an a | | | | |
| | 8 | | | | -STD-020 MSL | . Rating | | Peak Process Body Temperature Max Time at Pea | | | | | | | |
| | atte Tin (Sn) - annealed | | CU Alloy | N | NA . | | 0 | C | 30 | seconds 3 | | | | | |
| omments | | | | | | | | | | | | | | | |
| • • | ormation regarding material | | 1 6 4 | | | | | | | | | | | | |

| RoHS Material Composition Declaration | | | Declaration Type * | Detailed | | | | | |
|--|---|---|-----------------------------|------------|--|--|--|--|--|
| irective 2015/863/EU amending RoHS irective 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP). | | | | | | | | | |
| Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its uppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's Itability and the Company's remedies for issues that arise regarding information the Supplier provi | | | | | | | | | |
| RoHS Declaration * 4 - Item(s | s) does not contain RoHS restricted substance | ces per the definition above except for selected exer | nptions Supplier Acceptance | * Accepted | | | | | |
| Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead). Exemption: 7c-I Electrical and electronic components containing lead in a glass or ceramic other than dielectric ceramic in capacitors, e.g. piezoelectronic devices, or in a glass or ceramic matrix compound. | | | | | | | | | |
| Exemption List Version | EL-2011/534/EU | | | | | | | | |
| Declaration Signature | | | | | | | | | |
| Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester. | | | | | | | | | |
| Supplier Digital Signature R | | , | | | | | | | |

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

| Homogeneous Material | Weight | Unit of Measure | Level | Substance | CAS | Exempt | Weight | Unit of Measure |
|----------------------|--------|-----------------|----------|-----------------------------------|------------------|--------|----------|-----------------|
| Die | 1.095 | mg | Supplier | Silicon (Si) | 7440-21-3 | | 0.9855 | mg |
| | | | В | Nickel (Ni) | 7440-02-0 | | 0.0071 | mg |
| | | | Supplier | Gold (Au) | 7440-57-5 | | 0.0016 | mg |
| | | | Supplier | Lead Bisilicate | 65997-18-4 | 7c | 0.1007 | mg |
| Die Attach Solder | 3.5 | mg | Supplier | Silver (Ag) | 7440-22-4 | | 0.0875 | mg |
| | | | A | Lead (Pb) | 7439-92-1 | 7a | 3.2375 | mg |
| | | | Supplier | Tin (Sn) | 7440-31-5 | | 0.175 | mg |
| Lead Wire | 294.8 | mg | Supplier | Iron (Fe) | 7439-89-6 | | 0.2358 | mg |
| | | | Supplier | Copper (Cu) | 7440-50-8 | | 294.5052 | mg |
| | | | Supplier | Phosphorus (P) | 7723-14-0 | | 0.059 | mg |
| Marking Ink | 0.2 | mg | Supplier | Silicon Dioxide (SiO2) | 112945-52-5 | | 0.01 | mg |
| | | | Supplier | 1-Hydroxycyclohexyl phenyl ketone | 947-19-3 | | 0.01 | mg |
| | | | Supplier | Padimate (C14H21NO2) | 21245-01-2 | | 0.02 | mg |
| | | | Supplier | 2-Propenoic acid polymer | 53192-18-0 | | 0.13 | mg |
| | | | Supplier | Aluminum (Al) | 7429-90-5 | | 0.03 | mg |
| Mold Compound-Black | 38.0 | | | Metal Hydroxide | proprietary data | | 1.786 | mg |
| | | | Supplier | Carbon Black (C) | 1333-86-4 | | 0.114 | mg |
| | | | Supplier | Fused Silica (SiO2) | 60676-86-0 | | 30.4 | mg |
| | | | Supplier | Ortho-Cresol Novolac Resin | 29690-82-2 | | 3.8 | mg |
| | | | Supplier | Phenolic Resin (Novolac) | 9003-35-4 | | 1.9 | mg |
| Plating | 2.4 | mg | Supplier | Tin (Sn) | 7440-31-5 | | 2.4 | mg |