© Co	terial Composit opyright 2005. IPC, 1 national and Pan-An	Bannockb	urn, Illinois. A	Il rights reserved untions.	under both	This docume level parts, t	ent is a decla he declaratio	aration of on encom	f the substance npasses all lo	es with wer leve	in the manufactur el materials for wl	er listed it hich the m	em. Not anufactu	e: if the i arer has e	item is an asse	mbly with lowe sponsibility.
	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				e *	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materia					als and M	als and Mfg Information				
Supplier Information																
Company name*			Company unique ID			Unique ID Authority					Response Date*					
onsemi												2024-05-18				
Contact Name			Title - Contact				Phone - Contact*					Email - Contact*				
Product-Env-Stewards			Product Enviro Compliance			NA					Product-Env-Stewards@onsemi.com					
Authorized Representative*			Title - Representative			Phone - Representative*				Email - Representative*						
Product-Env-Stewards			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com						
Requester Item I	equester Item Number Mfr Iten		Number Mfr Item Name				Effective Date Version Manufacturing		facturing Site	Site Weigh			UOM	Unit Type		
	FSUSB20M		OMUX	HS-USB2.0 Switch			2024-05-18	3		CNS	CNS		25.8	:	mg	Each
Manufacturing Proce	ess Information	l												I		ł
Terminal Plating	Terminal Plating / Grid Array Material		erminal Base Alloy J-S		J-STD-020 MS	L Rating	Peak P	Peak Process Body Temperatu		ature M	ure Max Time at Peak Tem		nperature Number of Reflow Cycles		S	
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)		i) (no C	U Alloy 1		1		260		C	3	30 seco		onds 3			
Comments												-				
evel 1 - maximum time at j	peak temperature d	uring sol	dering is 10-3	0 seconds												
for more information rega	rding material com	position j	please refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth					
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of				
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted				
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all				
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.									
Supplier Digital Signature Ra	stislav Drska	Le							

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	1.35	mg	Supplier	Silicon (Si)	7440-21-3		1.35	mg	
Die Attach	0.33	mg	Supplier	Silver (Ag)	7440-22-4		0.2591	mg	
			Supplier	Phenolic Resin-2	54208-63-8		0.071	mg	
Lead Frame	11.68	mg	Supplier	Zinc (Zn)	7440-66-6		0.0127	mg	
			Supplier	Iron (Fe)	7439-89-6		0.3047	mg	
			Supplier	Copper (Cu)	7440-50-8		11.3372	mg	
			Supplier	Phosphorus (P)	7723-14-0		0.0254	mg	
Mold Compound-Black	12.3	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		1.23	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.123	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		10.947	mg	
Plating	0.02	mg	Supplier	Palladium (Pd)	7440-05-3		0.0007	mg	
			В	Nickel (Ni)	7440-02-0		0.0191	mg	
			Supplier	Gold (Au)	7440-57-5		0.0002	mg	
Wire Bond - Au	0.12	mg	Supplier	Gold (Au)	7440-57-5		0.12	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).