IPC ASSOCIATION CO	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			der both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lowe level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.								
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi				ials and Mfg Information				
upplier I	nformation				·									
Company name*			Company unique ID			J	Unique ID Authority				Response Date*			
nsemi										2024-05-14				
Contact Nam	ne	Title - Contact			I	Phone - Contact*				Email - Contact*				
Product-Env	v-Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com			
uthorized F	Representative*	Title - Representative			I	Phone - Representative*			Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com			
R	Requester Item Number	Mfr Item	Number	Mfr Item Name			Effective Date	Version	N	Anufacturing Site	Wei	ght*	UOM	Unit Type
		MBR2H100SFT3G 2A, 10		2A, 100 V SCHOT	2A, 100 V SCHOTTKY REC		2024-05-14		N	MY1			mg	Each
Ianufactı	uring Proccess Inform	ation												
Terminal Plating / Grid Array Material Terminal Base Alloy			Alloy J-S	STD-020 MSL	MSL Rating Peak Process Body Temperature Max Time at Peal				Temperature	Numbe	er of Reflow Cyc	les		
M	latte Tin (Sn) - annealed	C	CU Alloy	1			260		C	30	seconds	3		
omments														
vel 1 - maxi	imum time at peak tempera	ture during sol	dering is 10-3	30 seconds										
or more inf	formation regarding materia	al composition	please refer t	page 3										

RoHS Material Composition Declaration			Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledges that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.										
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted substance	s per the definition above except for selected exemp	tions Supplier Acceptance	* Accepted						
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.										
Supplier Digital Signature Ra	astislav Drska	-En								

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Clip	2.02	mg	Supplier	Zinc (Zn)	7440-66-6		0.0024	mg
			Supplier	Iron (Fe)	7439-89-6		0.0475	mg
			Supplier	Copper (Cu)	7440-50-8		1.9695	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0006	mg
Die	0.98	mg	Supplier	Silicon (Si)	7440-21-3		0.98	mg
Die Attach Solder	0.26	mg	Supplier	Silver (Ag)	7440-22-4		0.0065	mg
			A	Lead (Pb)	7439-92-1	7a	0.2405	mg
			Supplier	Tin (Sn)	7440-31-5		0.013	mg
Lead Frame	5.25	mg	Supplier	Zinc (Zn)	7440-66-6		0.0063	mg
			Supplier	Iron (Fe)	7439-89-6		0.1234	mg
			Supplier	Copper (Cu)	7440-50-8		5.1188	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0016	mg
Mold Compound-Black	5.79	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.579	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0289	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		0.8395	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		3.7635	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.579	mg
Plating	0.6	mg	Supplier	Tin (Sn)	7440-31-5		0.6	mg