ASDCIATION CONNECTING ELECTRANCE INDUSTRIES® INCLUSTRIES	C. Bannockł	ourn. Illinois. A	Il rights reserved untions.	under both	This docume level parts, t	ent is a declarat he declaration of	ion of the su	ubstances s all lowe	within the m r level mater	nanufacture rials for wh	er listed iten ich the mar	n. Note: i ufacture	if the item is an as r has engineering	sembly with lowe responsibility.
				Form Type Distribute	*	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information			
Supplier Information														
Company name* Co			Company unique ID			Unique ID Authority					Response Date*			
onsemi										2024-05-10				
Contact Name	ntact Name Title - Contact				Phone - Contact*						Email - Contact*			
Product-Env-Stewards Product En			ct Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Authorized Representative* Title - R			le - Representative			Phone - Representative*				Email - Representative*				
Product-Env-Stewards Pro			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Requester Item Number	Mfr Item Number		umber Mfr Item Name			Effective Date	Version	N	Manufacturing Site		We	ight*	UOM	Unit Type
	MC78L0	MC78L08ABDR2G ANA 100		A 100MA 8V VREG		2024-05-10			CNW		71.	99	mg	Each
Manufacturing Proccess Information	ion													
Terminal Plating / Grid Array Ma	id Array Material Terminal Base Alloy		Alloy	J-STD-020 MSI	TD-020 MSL Rating		Peak Process Body Temperature M		re Max Tim	Max Time at Peak Tempera		nperature Number of Reflow Cycles		les
Matte Tin (Sn) - annealed CU Alloy			1		260		С	30		seconds	3			
Comments														
evel 1 - maximum time at peak temperatu	re during so	Idering is 10-3	0 seconds											
or more information regarding material	composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	(Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Disobutyl phthalate (DIBP).											
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of							
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted								
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.												
Exemption List Version	EL-2011/534/EU											
Declaration Signature												
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the							
Supplier Digital Signature Ra	stislav Drska	Le										

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	1.33	mg	Supplier	Silicon (Si)	7440-21-3		1.33	mg	
Die Attach	2.4	mg	Supplier	Silver (Ag)	7440-22-4		1.8	mg	
			Supplier	Epoxy resins	129915-35-1		0.6	mg	
Lead Frame :	37.61	mg	Supplier	Silver (Ag)	7440-22-4		0.2257	mg	
			Supplier	Zinc (Zn)	7440-66-6		0.0451	mg	
			Supplier	Iron (Fe)	7439-89-6		0.8838	mg	
			Supplier	Copper (Cu)	7440-50-8		36.4441	mg	
			Supplier	Phosphorus (P)	7723-14-0		0.0113	mg	
Mold Compound-Black	28.58	mg		Epoxy resin	proprietary data		1.429	mg	
			Supplier	Phenolic Resin	Proprietary Data		1.429	mg	
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.5716	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.1429	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		25.0075	mg	
Plating	1.89	mg	Supplier	Tin (Sn)	7440-31-5		1.89	mg	
Wire Bond - Cu	0.18	mg	Supplier	Copper (Cu)	7440-50-8		0.18	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).