IPC - ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.											
752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Typhttp://www.ipc.org/IPC-175x Distribute				e *	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ials and Mfg Information				
upplier Inform	ation														
Company name*			Company unique ID			τ	Unique ID Authority					Response Date*			
onsemi												2024-05-18			
Contact Name			Title - Contact]	Phone - Contact*				Email - Contact*				
Product-Env-Stewards			Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com			
Authorized Representative*			Title - Representative			1	Phone - Representative*				Email - Representative*				
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Requester	r Item Number	Mfr Item Number		Mfr Item Name			Effective Date	Versi	on	Manufacturing Site		,	Weight*	UOM	Unit Type
	MJL21196G		96G	BIP T0264 NPN 16A 250V FG			2024-05-18	4-05-18 KR8		:	10737.244	mg	Each		
	Process Informatio		. 10		OED 020 110	I D	D 1 D	D. I	m] A		The state of the s		SD G	,
3			· · · · · · · · · · · · · · · · · · ·		-STD-020 MS	L Rating		Process Body Temperature Max Time at Peak					cles		
	1 (Sn) - annealed	C	U Alloy	IN IN	A		0		IC.	30		secon	ds 3		
omments															
	•• • • •	•.•													
r more informatio	on regarding material co	mposition p	please refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU											
cadmium, hexavalentchromium, polybrominal contains a RoHS restricted substance inexcess encompass all such components. Supplier certi as of the date that Supplier completes this for Company acknowledges that Supplier may ha independently verified information provided by certification in this paragraph. If the Company	ted biphenyls and/or polybrominated dipheny of an applicable quantity limit, please indicate fies that it gathered the information it provident. Supplier acknowledges that Company will we relied on information provided by others in the supplier agrees that, at a minimum and the Supplier enter into a written agreements ource of the Supplier's liability and the Com-	2011/65/EU and implemented by the laws of the End ethers (each a "RoHS restricted substance") in except the below which, if any, RoHS exemption you believe in this form using appropriate methods to ensure rely on this certification in determining the compliant completing this form, and that Supplier may not have its suppliers have provided certifications regarding ent with respect to the identified part, the terms and capany's remedies for issues that arise regarding information in the provided certification in	sess of the applicable quantity limit identified able may apply. If the part is an assembly with low its accuracy and that such information is true annee of its products with European Union member ave independently verified such information. However, their contributions to the part, and those certifications of that agreement, including any warr	bove. If a homogeneous material within the part ver level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. It is involved in situations where Supplier has not ations are at least as comprehensive as the ranty rights and/or remedies provided as part of							
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted substance	s per the definition above except for selected exemp	tions Supplier Acceptance	* Accepted							
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required f Requester) and click on Submit Form to ha		Accepted" on the Supplier Acceptance drop-dow	n. This will display the signature area. Digita	lly sign the declaration (if required by the							
Supplier Digital Signature Ra	astislav Drska	-En									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.004	mg	Supplier	Silicon (Si)	7440-21-3		0.004	mg
Die Attach	438.49	mg	A	Lead (Pb)	7439-92-1	7a	416.5655	mg
			Supplier	Tin (Sn)	7440-31-5		21.9245	mg
Lead Frame	6869.64	mg	Supplier	Zinc (Zn)	7440-66-6		6.8696	mg
			Supplier	Iron (Fe)	7439-89-6		6.8696	mg
			Supplier	Copper (Cu)	7440-50-8		6855.9009	mg
Mold Compound-Black	3393.27	mg		Brominated epoxy resin	proprietary data		135.7308	mg
			Supplier	Phenolic Resin	Proprietary Data		173.0568	mg
			В	Antimony Trioxide (Sb2O3)	1309-64-4		44.1125	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		2694.2566	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		346.1133	mg
Plating	34.3	mg	Supplier	Tin (Sn)	7440-31-5		34.3	mg
Wire Bond - Al	1.54	mg	Supplier	Aluminum (Al)	7429-90-5		1.54	mg