ASSOCIATION CONNE	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
1752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				e * Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ous Materia	als and Mf	g Informa	ntion	
Supplier Info	ormation						·								
Company name*			Company un	Company unique ID			Unique ID Authority					Response Date*			
onsemi												2024-05-14			
Contact Name		Title - Contact			I	Phone - Contact*					Email - Contact*				
Product-Env-St	tewards	Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com				
uthorized Rep	presentative*	Title - Repres	Title - Representative			Phone - Representative*				Email - Representative*					
Product-Env-St	tewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
Requ	uester Item Number	Mfr Iter	tem Number Mfr Item Name				Effective Dat	e Versio	Version Manufacturing Site		ng Site	W	eight*	UOM	Unit Type
		MM74HCT74MTCX Dua		Dual D-Type FF W/Pre/Clr			2024-05-14	2024-05-14 PH1			45.24		mg	Each	
<b>Ianufacturi</b>	ing Proccess Informa	ation												·	
Term	ninal Plating / Grid Array M	al Plating / Grid Array Material		Terminal Base Alloy		-020 MSL Rating		Peak Process Body Temperatu		re Max Time at Peak Temper		Temperatu	ature Number of Reflow Cycles		les
Preci Sn)	Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)		CU Alloy 1		1		260		C	30 seco		second	s <b>3</b>		
Comments															
vel 1 - maximu	um time at peak temperat	ture during so	oldering is 10-3	0 seconds											
or more inforn	mation regarding materia	l composition	please refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU  RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on informationprovided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its uppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	2.0	mg	Supplier	Silicon (Si)	7440-21-3		2	mg
Die Attach	1.44	mg		Epoxy resin	proprietary data		0.144	mg
			Supplier	Silver (Ag)	7440-22-4		1.152	mg
			Supplier	Formaldehyde Polymer	9003-36-5		0.144	mg
Lead Frame	22.54	mg	Supplier	Iron (Fe)	7439-89-6		0.4283	mg
			Supplier	Copper (Cu)	7440-50-8		22.1117	mg
Mold Compound-Black	19.0			Epoxy resin	proprietary data		0.95	mg
			Supplier	Phenolic Resin	Proprietary Data		0.95	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.38	mg
			Supplier	Carbon Black (C)	1333-86-4		0.095	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		16.625	mg
Plating	0.04		Supplier	Palladium (Pd)	7440-05-3		0.003	mg
			В	Nickel (Ni)	7440-02-0		0.0364	mg
			Supplier	Gold (Au)	7440-57-5		0.0006	mg
Wire Bond - Cu	0.22	mg	Supplier	Copper (Cu)	7440-50-8		0.22	mg