	N CONNECTING S INDUSTRIES® MALE TABLE	osition Dee PC, Bannockb n-American co	claration ourn, Illinois. A opyright conver	Il rights reserved untions.	under both	This docume level parts, t	ent is a declarati he declaration e	on of the subst ncompasses all	ances within the m lower level mater	nanufacturer l ials for which	listed item. Not h the manufactu	te: if the item is an a urer has engineering	ssembly with lowe responsibility.	
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form 7				Form Type Distribute	e * Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater				us Materials	als and Mfg Information			
Supplier	r Information													
Company name* Company un				ique ID			Unique ID Authority				Response Date*			
onsemi											2024-05-18			
Contact N	lame	Title - Contact			]	Phone - Contact*				Email - Contact*				
Product-H	Env-Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com			
uthorize	ed Representative*	Title - Representative			]	Phone - Representative*			E	Email - Representative*				
Product-Env-Stewards			Product Enviro Compliance				NA			Р	Product-Env-Stewards@onsemi.com			
	Requester Item Number Mfr Item Number Mfr Item Name   MPSA29 BIPOLAR TRAN		Number Mfr Item Name				Effective Date	Version	Manufacturin	ng Site	Weight*	UOM	Unit Type	
			SISTOR TO-92	2	2024-05-18 CNF			223.092	mg	Each				
/Ianufa	cturing Proccess Informa	tion						-				I		
	Terminal Plating / Grid Array Material		Cerminal Base Alloy J-STD-020 M		J-STD-020 MSI	L Rating	Peak Process Body Temperatur		erature Max Tim	e at Peak Ter	mperature Nu	umber of Reflow Cy	cles	
Matte Tin (Sn) - annealed C		CU Alloy NA			0 C 3		30		seconds 3					
omments	6													
o <b>r more</b> i	information regarding material	composition	please refer to	page 3										

RoHS Material Composition Declaration				Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	ctive 2011/65/EU (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of							
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted							
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all							
Exemption List Version	EL-2011/534/EU											
Declaration Signature												
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the							
Supplier Digital Signature Ra	stislav Drska	Le										

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless	otherwise noted).							
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.075	mg	Supplier	Silicon (Si)	7440-21-3		0.075	mg
Lead Frame	101.001	mg	Supplier	Silver (Ag)	7440-22-4		1.01	mg
			Supplier	Manganese (Mn)	7439-96-5		0.505	mg
			В	Nickel (Ni)	7440-02-0		0.182	mg
			Supplier	Iron (Fe)	7439-89-6		98.4	mg
			Supplier	Copper (Cu)	7440-50-8		0.904	mg
Mold Compound-Black	112.0	mg	Supplier	2,6-dibromo-4-[1-(3-bromo-4- hydroxyphenyl)-1-methylethyl]phenol	6386-73-8		3.36	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		22.4	mg
			В	Antimony Trioxide (Sb2O3)	1309-64-4		2.8	mg
			Supplier	Carbon Black (C)	1333-86-4		0.84	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		82.6	mg
Plating	9.94	mg	Supplier	Tin (Sn)	7440-31-5		9.94	mg
Wire Bond - Au	0.076	mg	Supplier	Gold (Au)	7440-57-5		0.076	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).