ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES INDUSTRIES	omposition De 005. IPC, Bannockt 1d Pan-American co	claration ourn, Illinois. A opyright conve	All rights reserved u ntions.	nder both	This docume level parts, th	ent is a declarati he declaration e	on of the subst ncompasses all	ances within lower level r	the manufactur naterials for wl	er listed iter hich the mar	n. Note: if ufacturer	f the item is an as has engineering	sembly with low responsibility.
	IPC Web Site for Information on IPC-1752 Standard Form http://www.ipc.org/IPC-175x Distri				 * Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater 				ials and Mfg Information				
upplier Information													
ompany name*	Company unique ID			l	Unique ID Authority				Response Date*				
nsemi									2024-05-14				
ontact Name	Title - Contact			1	Phone - Contact*				Email - Contact*				
Product-Env-Stewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
uthorized Representative*	Title - Repre	Title - Representative			Phone - Representative*				Email - Representative*				
roduct-Env-Stewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Requester Item Number	Mfr Item	Number	Mfr Item Name			Effective Date	Version	Manufac	Manufacturing Site		ight*	UOM	Unit Type
	MUR210	MUR2100ERLG REC SURM 2		A 1KV ULTFST TR		2024-05-14		CNP	CNP).99	mg	Each
Ianufacturing Proccess Info	rmation												
Terminal Plating / Grid Arr	Terminal Plating / Grid Array Material Terr		erminal Base Alloy J-STD-020 MSL		L Rating	Peak Process Body Temperatu		erature Max	Time at Peak	Temperatur	e Numb	er of Reflow Cyc	les
Matte Tin (Sn) - annealed		CU Alloy NA		NA		0 C 30			seconds	3			
omments													
or more information regarding mat	erial composition	please refer to	page 3										

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	(Pb), Mercury (Hg), Hexavalent Chro	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Disobutyl phthalate (DIBP).									
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted						
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).								
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required Requester) and click on Submit Form to h			e drop-dowi	a. This will display the signature area. Digita	lly sign the declaration (if required by the						
Supplier Digital Signature	astislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.18	mg	Supplier	Silicon (Si)	7440-21-3		0.18	mg
Die Attach Solder	7.98	mg	Supplier	Silver (Ag)	7440-22-4		0.1995	mg
			А	Lead (Pb)	7439-92-1	7a	7.3815	mg
			Supplier	Tin (Sn)	7440-31-5		0.399	mg
Lead Frame	125.08	mg	В	Nickel (Ni)	7440-02-0		0.2502	mg
			Supplier	Copper (Cu)	7440-50-8		124.8298	mg
Mold Compound-Black	116.8	mg		Metal Hydroxide	proprietary data		5.84	mg
			Supplier	Carbon Black (C)	1333-86-4		1.168	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		87.6	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		11.68	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		10.512	mg
Plating	0.95	mg	Supplier	Tin (Sn)	7440-31-5		0.95	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3