ASSOCIATION CONNECTING LECTRONICS INDUSTRIES® International and Pa	PC, Bannockt	ourn, Illinois. A	Il rights reserved untions.	nder both	This docum level parts, t	ent is a declarat the declaration of	ion of the su encompasse	ubstances s all lowe	within the manufactu r level materials for w	rer listed	item. Note: i nanufacture	f the item is an as t has engineering	ssembly with lower responsibility.	
					Type * Declaration Class * ute Class 6 - RoHS Yes/No, Homogeneous Materi				als and Mfg Information					
Supplier Information														
Company name*		Company unique ID				Unique ID Authority					Response Date*			
onsemi										2024-05	2024-05-15			
Contact Name Title - Co			itle - Contact			Phone - Contact*				Email -	Email - Contact*			
Product-Env-Stewards Prod			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Authorized Representative* Title			Title - Representative			Phone - Representative*			Email -	Email - Representative*				
Product-Env-Stewards Pr			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Requester Item Number	Mfr Item	Number	Mfr Item Name			Effective Date	Version	1	Manufacturing Site		Weight*	UOM	Unit Type	
	MURA1	IURA110T3G REC SMA		SMA 1A 100V ULTFST TR		2024-05-15		(CNP		76.66	mg	Each	
Manufacturing Proccess Informa	tion		·											
Terminal Plating / Grid Array M	Terminal Plating / Grid Array Material Terminal Base		Alloy J	J-STD-020 MSL	Rating	Peak Proc	ess Body T	emperatu	re Max Time at Peak	Tempera	ture Numb	er of Reflow Cy	cles	
Matte Tin (Sn) - annealed CU Alloy		CU Alloy	1	1		260		С	30	seco	nds 3			
Comments														
level 1 - maximum time at peak temperat	ure during sol	ldering is 10-3	0 seconds											
For more information regarding material	composition	please refer to	o page 3											

RoHS Material Composition Declar	ation			Declaration Type *	Detailed
Directive 2015/863/EU amending Rol Directive 2011/65/EU	(Pb), Mercury (Hg), Hexav		ninated Biphenyls (PBB), Polybror	dmium and quantity limit of 0.1% by mass (100 ninated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polyb contains a RoHS restricted substance i encompass all such components.Suppl as of the date that Supplier completes Company acknowledges that Supplier independently verified information pro- certification in this paragraph.If the Co	rominated biphenyls and/or polybror nexcess of an applicable quantity lim ier certifies that it gathered the inforr this form.Supplier acknowledges that may have relied on informationprovi ovided by others, Supplier agrees that ompany and the Supplier enter into a clusivesource of the Supplier's liabili	ninated diphenyl ethers (each a "R it, please indicate below which, if nation it provides in this form usin Company will rely on this certifud ded by others in completing this f , at a minimum, itssuppliers have written agreement with respect to ty and the Company's remedies for	toHS restricted substance") in exce any, RoHS exemption you believe ag appropriate methods to ensure it cation in determining the complian orm, and that Supplier may not hav provided certifications regarding th the identified part,the terms and co or issues that arise regarding inform	ropean Union member states) of the part identifies so of the applicable quantity limit identified about may apply. If the part is an assembly with lows a accuracy and that such information is true and ce of its products with European Union member re independently verified such information. How heir contributions to the part, and those certifica motions of that agreement, including any warra nation the Supplier provides in this form. In the	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the inty rights and/or remedies provided as part of
RoHS Declaration * 4	- Item(s) does not contain RoHS restr	icted substances per the definition	above except for selected exempti	ons Supplier Acceptance	* Accepted
Exemption: 7a: Lead in high meltin Exemption: 7c-I Electrical and elect	g temperature type solders (i.e. lead ronic components containing lead i	l based solder alloys containing n a glass or ceramic other than	85% by weight or more lead). dielectric ceramic in capacitors, o	e.g. piezoelectronic devices, or in a glass or ce	eramic matrix compound.
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the rec Requester) and click on Submit For			Supplier Acceptance drop-down	. This will display the signature area. Digital	ly sign the declaration (if required by the
Supplier Digital Signature	Rastislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Clip	7.0	mg	Supplier	Zinc (Zn)	7440-66-6		0.014	mg
			В	Nickel (Ni)	7440-02-0		0.0252	mg
			Supplier	Iron (Fe)	7439-89-6		0.1778	mg
			Supplier	Copper (Cu)	7440-50-8		6.7725	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0105	mg
Die	1.12	mg	Supplier	Silicon (Si)	7440-21-3		1.1088	mg
			Supplier	Lead Bisilicate	65997-18-4	7c	0.0112	mg
Die Attach Solder	3.45	mg	Supplier	Silver (Ag)	7440-22-4		0.0862	mg
			А	Lead (Pb)	7439-92-1	7a	3.1913	mg
			Supplier	Tin (Sn)	7440-31-5		0.1725	mg
Lead Frame	28.84	mg	Supplier	Zinc (Zn)	7440-66-6		0.0346	mg
			Supplier	Iron (Fe)	7439-89-6		0.6922	mg
			Supplier	Copper (Cu)	7440-50-8		28.0902	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0231	mg
Mold Compound-Black	34.87	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		3.487	mg
			Supplier	Carbon Black (C)	1333-86-4		0.1743	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		5.0561	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		22.6655	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		3.487	mg
Plating	1.38	mg	Supplier	Tin (Sn)	7440-31-5		1.38	mg