© Copyright 2005. IPC	Copyright 2005 IPC Bannockburn Illinois All rights reserved under both					This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.							
	2-21.1 IPC Web Site for Information on IPC-1752 Standard Form T http://www.ipc.org/IPC-175x Distribution				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mf					Afg Informat	ion		
Supplier Information													
Company name*	Company unique ID			Unique ID Authority					Response Date*				
onsemi									2024-05-11				
Contact Name Title - Contact			ct		Phone - Contact*					Email - Contact*			
Product-Env-Stewards Product E			oduct Enviro Compliance			NA				Product-Env-Stewards@onsemi.com			
Authorized Representative* Title - Re			e - Representative			Phone - Representative*			Email - Representative*				
Product-Env-Stewards Pro			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com			
Requester Item Number	Requester Item Number Mfr Item N		Number Mfr Item Name			Effective Date	Version	1	Manufacturing Site		Weight*	UOM	Unit Type
	NCP432	ICP432BISNT1G Programmable Pre		ecision Referen	ces	2024-05-11 MY1		MY1		8.14	mg	Each	
Manufacturing Proccess Information	n		·								•		
Terminal Plating / Grid Array Material Terminal Base Alloy		Alloy J	J-STD-020 MSI	L Rating	Peak Proc	ess Body Te	emperatu	re Max Time at Peak	Tempera	ature Numb	per of Reflow Cyd	cles	
Matte Tin (Sn) - annealed CU Alloy 1			1		260		С	30	seco	nds 3			
Comments													
level 1 - maximum time at peak temperature	during sol	dering is 10-3	0 seconds										
For more information regarding material co	mposition	please refer to	o page 3										

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted	
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless								
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.16	mg	Supplier	Silicon (Si)	7440-21-3		0.16	mg
Die Attach Epoxy	0.18	mg		Epoxy resin	proprietary data		0.117	mg
			Supplier	Aluminum Trioxide (Al2O3)	1344-28-1		0.063	mg
Lead Frame	2.75	mg	Supplier	Silver (Ag)	7440-22-4		0.0589	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0036	mg
			Supplier	Iron (Fe)	7439-89-6		0.066	mg
			Supplier	Copper (Cu)	7440-50-8		2.6194	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0022	mg
Mold Compound-Black	4.9	mg		Epoxy resin	proprietary data		0.245	mg
			Supplier	Phenolic Resin	Proprietary Data		0.245	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.098	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0245	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		4.2875	mg
Plating	0.14	mg	Supplier	Tin (Sn)	7440-31-5		0.14	mg
Wire Bond	0.01	mg	Supplier	Palladium (Pd)	7440-05-3		0.0001	mg
			Supplier	Copper (Cu)	7440-50-8		0.0099	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).