IPC ASSOCIATION CONNECT ELECTRONICS INDUSTR	Material Composi © Copyright 2005. IPC, international and Pan-A	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lowe level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.								
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ials and Mfc Information			
upplier Infor	mation													
Company name*			Company unique ID			Ţ	Unique ID Authority				Response Date*			
nsemi											2024-05-15			
Contact Name		Tit	Title - Contact			I	Phone - Contact*				Email - Contact*			
Product-Env-Stev	wards	Pro	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com			
uthorized Repre	sentative*	Tit	Title - Representative			I	Phone - Representative*				Email - Representative*			
Product-Env-Stev	wards	Pro	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com			
Reques	Requester Item Number Mfr Iter		tem Number Mfr Item Name				Effective Date	e Versi	on	Manufacturing Site	V	Veight*	UOM	Unit Type
		NCP45540IMNTWG- NCP45540IMNTW		WG-L		2024-05-15		UTH		2	8.22	mg	Each	
Ianufacturing	g Proccess Informatio	n							,					
Terminal Plating / Grid Array Material Termin			rminal Base Alloy J-STD-020 MSI		SL Rating	Peak Process Body Temperature Max Time a		re Max Time at Peak	Temperatu	are Numb	ber of Reflow Cyc	les		
Matte Tin (Sn) - annealed		CU A	CU Alloy 3		}		260	260 C		30	second	ds 3		
omments														
FTENTION: MS	SL 3 Rated item requires B	ake and Dry P	Pack (after	electrical test)										
or more informa	tion regarding material cor	mposition plea	ase refer to	page 3										

RoHS Material Composition Declaration			Declaration Type *	Detail	led						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substa	ances per the definition above	Supplier Ac	ceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructional Complete all of the required	fields on all neggs of this form. Calcut th		a duan dawn. This will display the signature on	a Digitally sign	the declaration (if recruired by the						
Instructions: Complete all of the required Requester) and click on Submit Form to			e drop-down. This will display the signature ar	ea. Digitally sign	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	1.29	mg	Supplier	Silicon (Si)	7440-21-3		1.29	mg
Die Attach	0.12	mg		Resin	proprietary data		0.0096	mg
			Supplier	Silver (Ag)	7440-22-4		0.1014	mg
			Supplier	Formaldehyde Polymer	9003-36-5		0.009	mg
Lead Frame	12.38	mg	Supplier	Silver (Ag)	7440-22-4		0.2476	mg
			Supplier	Tin (Sn)	7440-31-5		0.031	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0272	mg
			Supplier	Chromium (Cr)	7440-47-3		0.031	mg
			Supplier	Copper (Cu)	7440-50-8		12.0433	mg
Mold Compound-Black	13.55		Supplier	Epoxy and Phenolic Resin	40216-08-8		1.084	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0677	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		0.271	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		11.7207	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.4065	mg
Plating	0.44	mg	Supplier	Tin (Sn)	7440-31-5		0.44	mg
Wire Bond - Au	0.44	mg	Supplier	Gold (Au)	7440-57-5		0.44	mg