© C	Aterial Composit Copyright 2005. IPC, 1 ernational and Pan-Am	Bannockbi	urn, Illinois. A	Ill rights reserved untions.	under both	This docum level parts,	ent is a decla the declaratio	ration of on encom	the substance passes all low	s within the materi	anufacture als for wh	er listed ite hich the m	em. Note anufactur	: if the item is a rer has enginee	an assembly with lowe ring responsibility.	
					Form Type Distribute	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ıs Materia	ials and Mfg Information				
Supplier Informatio	n															
Company name*			Company unique ID			Unique ID Authority					Response Date*					
onsemi												2024-05-10				
Contact Name			Title - Contact				Phone - Contact*					Email - Contact*				
Product-Env-Stewards			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com						
Authorized Representative*			Title - Representative			Phone - Representative*				Email - Representative*						
Product-Env-Stewards			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com						
Requester Iten	Requester Item Number Mfr Item		Number Mfr Item Name				Effective D	ate Ve	rsion	Manufacturing Site		v	/eight*	UOM	Unit Type	
		NCV210RSQT2G		CURRENT SENSE AMP G=200		0	2024-05-10	-		MY1		8	.95	mg	Each	
Manufacturing Proc	ccess Information	I										<u>,</u>				
Terminal Plating / Grid Array Material Termin			erminal Base A	al Base Alloy J-STD-020 MSL R		L Rating	Peak P	Peak Process Body Temperature Max		ire Max Time	e at Peak '	ak Temperature Number of		mber of Reflow	Cycles	
Matte Tin (Sn) - annealed CU Alloy			U Alloy		1		260		С	30		second	ls 3			
Comments																
level 1 - maximum time a	t peak temperature d	uring sole	dering is 10-3	0 seconds												
For more information reg	garding material com	position p	olease refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).										
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure		
Die	0.38	mg	Supplier	Silicon (Si)	7440-21-3		0.38	mg		
Die Attach Epoxy	0.06	mg		Epoxy resin	proprietary data		0.039	mg		
			Supplier	Aluminum Trioxide (Al2O3)	1344-28-1		0.021	mg		
Lead Frame	4.43	mg	Supplier	Silver (Ag)	7440-22-4		0.1107	mg		
			Supplier	Zinc (Zn)	7440-66-6		0.0044	mg		
			Supplier	Iron (Fe)	7439-89-6		0.1063	mg		
			Supplier	Copper (Cu)	7440-50-8		4.2085	mg		
Mold Compound-Black	3.55	mg		Epoxy resin	proprietary data		0.1775	mg		
			Supplier	Phenolic Resin	Proprietary Data		0.1775	mg		
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.071	mg		
			Supplier	Carbon Black (C)	1333-86-4		0.0177	mg		
			Supplier	Fused Silica (SiO2)	60676-86-0		3.1063	mg		
Plating	0.5	mg	Supplier	Tin (Sn)	7440-31-5		0.5	mg		
Wire Bond - Au	0.03	mg	Supplier	Gold (Au)	7440-57-5		0.03	mg		

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).