	CONNECTING INDUSTRIES* International and Pan-A	, Bannockb	ourn, Illinois. A	ll rights reserved untions.	under both	This docum level parts, t	ent is a declar the declaration	ation of t	he substance asses all low	es within the manu ver level materials	facturer liste for which th	ed item. Note: if le manufacturer	the item is an a has engineering	ssembly with lower responsibility.	
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				Form Type ⁵ Distribute	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					Aaterials and	ials and Mfg Information			
Supplier	Information				· ·		· · ·								
Company name* Co				Company unique ID			Unique ID Authority					Response Date*			
onsemi												2024-05-18			
Contact Na	ame	Title - Contact				Phone - Contact*				Ema	Email - Contact*				
Product-E	nv-Stewards		Product Enviro Compliance				NA				Prod	Product-Env-Stewards@onsemi.com			
Authorized	Representative*	Title - Representative			Phone - Representative*				Ema	Email - Representative*					
Product-E	Product-Env-Stewards			Product Enviro Compliance			NA				Prod	Product-Env-Stewards@onsemi.com			
	Requester Item Number	Number Mfr Item Name				Effective Da	Effective Date Version Manufacturing Si		ite	Weight* UC		Unit Type			
	NCV8170BXV2 G		0BXV250T2	2 Ultra-Low IQ 150 mA CMOS LDO Regulator, High Ohmic State, Vout=2.5V, automotive			2024-05-18			CN1		2.79	mg	Each	
Manufac	turing Proccess Informatio	n													
r	Terminal Plating / Grid Array Material Te			erminal Base Alloy J-STD-020 MSL		Rating	Peak Process Body Temperature Max Time at		Peak Temp	ak Temperature Number of Reflow Cycles					
Matte Tin (Sn) - annealed CU Alloy				1		260		С	30	se	conds 3				
Comments															
evel 1 - ma	aximum time at peak temperature	during sol	ldering is 10-3	0 seconds											
for more in	nformation regarding material con	mposition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU												
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of							
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted								
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all							
Exemption List Version	EL-2011/534/EU											
Declaration Signature												
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the							
Supplier Digital Signature Ra	stislav Drska	Le										

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).											
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure			
Die	0.12	mg	Supplier	Silicon (Si)	7440-21-3		0.12	mg			
Lead Frame	1.18	mg	В	Nickel (Ni)	7440-02-0		0.4283	mg			
			Supplier	Iron (Fe)	7439-89-6		0.5924	mg			
			Supplier	Copper (Cu)	7440-50-8		0.1593	mg			
Mold Compound-Black	1.4	mg	Supplier	Boron zinc hydroxide oxide	138265-88-0		0.042	mg			
			Supplier	Zinc Monoxide (ZnO)	1314-13-2		0.007	mg			
			Supplier	2,4,6-triamino-s-triazincompd.withs- triazine-triol	37640-57-6		0.042	mg			
			Supplier	Silica Amorphous (SiO2)	7631-86-9		1.12	mg			
			Supplier	Carbon Black (C)	1333-86-4		0.014	mg			
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		0.112	mg			
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.063	mg			
Plating	0.06	mg	Supplier	Tin (Sn)	7440-31-5		0.06	mg			
Wire Bond - Au	0.03	mg	Supplier	Gold (Au)	7440-57-5		0.03	mg			

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).