ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES®	Material Composit © Copyright 2005. IPC, 1 international and Pan-An	Bannockb	urn, Illinois. A	Il rights reserved untions.	under both	This docum level parts,	ent is a decla the declaratic	ration of n encom	the substances passes all low	s within the mar er level materia	nufacture ls for whi	r listed iter ich the ma	n. Note: i nufacture	if the item is an as r has engineering	ssembly with lower responsibility.
1752-21.1					Form Type Distribute	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					Material	ials and Mfg Information			
Supplier Informa	ation														
Company name*			Company unique ID			Unique ID Authority					Response Date*				
onsemi												2024-05-18			
Contact Name			Title - Contact				Phone - Contact*					Email - Contact*			
Product-Env-Stewards			Product Enviro Compliance			NA					Product-Env-Stewards@onsemi.com				
Authorized Representative*			Title - Representative			Phone - Representative*					Email - Representative*				
Product-Env-Stewards			Product Enviro Compliance			NA					Product-Env-Stewards@onsemi.com				
Requester Item Number Mfr Item		Mfr Item	Number Mfr Item Name				Effective D	ate Vei	rsion	Manufacturing Site		W	eight*	UOM	Unit Type
		NTK3139PT1G F		PFET SOT723 20V 780MA 0.4			2024-05-18			CN1		1.2	275	mg	Each
Manufacturing P	Proccess Information	l													
Terminal Plating / Grid Array Material Termina			erminal Base A	Base Alloy J-STD-020 MSL			Peak Process Body Temperature Max Time at Pe		at Peak T	k Temperature Number of Reflow Cycles					
Matte Tin (Sn) - annealed CU Alloy			U Alloy		1		260		С	30		seconds	3		
Comments															
level 1 - maximum tin	ne at peak temperature d	luring sol	dering is 10-3	0 seconds											
For more information	n regarding material com	position p	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth					
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of				
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted				
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all				
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.									
Supplier Digital Signature Ra	stislav Drska	Le							

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	0.13	mg	Supplier	Silicon (Si)	7440-21-3		0.13	mg	
Lead Frame	0.28	mg	Supplier	Silver (Ag)	7440-22-4		0.0255	mg	
			В	Nickel (Ni)	7440-02-0		0.103	mg	
			Supplier	Iron (Fe)	7439-89-6		0.1414	mg	
			Supplier	Copper (Cu)	7440-50-8		0.0101	mg	
Mold Compound-Black	0.86	mg	Supplier	Boron zinc hydroxide oxide	138265-88-0		0.0258	mg	
			Supplier	Zinc Monoxide (ZnO)	1314-13-2		0.0043	mg	
			Supplier	2,4,6-triamino-s-triazincompd.withs- triazine-triol	37640-57-6		0.0258	mg	
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.688	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.0086	mg	
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		0.0688	mg	
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.0387	mg	
Plating	0.003	mg	Supplier	Tin (Sn)	7440-31-5		0.003	mg	
Wire Bond - Cu	0.002	mg	Supplier	Copper (Cu)	7440-50-8		0.002	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).