	Material Composit © Copyright 2005. IPC, I international and Pan-An	Bannockb	urn, Illinois. A	ll rights reserved untions.	under both	This docume level parts, t	ent is a decla he declaratio	ration of t	the substances passes all lowe	within th er level m	e manufactur aterials for wl	er listed it hich the m	em. Not anufact	te: if the urer has	item is an ass engineering re	embly with lowe esponsibility.
	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				*	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					als and Mfg Information					
Supplier Informat	ion															
Company name*			Company unique ID			Unique ID Authority					Response Date*					
onsemi										2024-05-14						
Contact Name	Title - Contact				Phone - Contact*					Email - Contact*						
Product-Env-Stewards	Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com						
Authorized Representa	Title - Representative			Phone - Representative*				Email - Representative*								
Product-Env-Stewards			Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com				
Requester It	Requester Item Number Mfr Item			Number Mfr Item Name			Effective D	Effective Date Version Manufacturing Sit		uring Site	Weight*		:	UOM	Unit Type	
	NV25040		DTHFT3G	T3G 4KB SPI SER CMOS EEPROM TSSOP8			2024-05-14	+		PH1		3	1.2		mg	Each
Manufacturing Pr	occess Information	L					·									
Terminal Pla	Terminal Plating / Grid Array Material		erminal Base A	rminal Base Alloy J-STI		Rating	Peak P	Peak Process Body Tempera		ture Max Time at Peak T		Temperature Number		umber of	nber of Reflow Cycles	
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)			U Alloy	alloy 1			260		С	30 seco		second	conds 3			
Comments																
evel 1 - maximum time	e at peak temperature d	luring sol	dering is 10-3	0 seconds												
or more information	regarding material com	position j	please refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU												
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of							
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted							
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all							
Exemption List Version	EL-2011/534/EU											
Declaration Signature												
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the							
Supplier Digital Signature Ra	stislav Drska	Le										

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.66	mg	Supplier	Silicon (Si)	7440-21-3		0.66	mg
Die Attach	0.12	mg		Epoxy resin	proprietary data		0.012	mg
			Supplier	Silver (Ag)	7440-22-4		0.096	mg
			Supplier	Formaldehyde Polymer	9003-36-5		0.012	mg
Lead Frame	10.96	mg	Supplier	Zinc (Zn)	7440-66-6		0.0132	mg
			Supplier	Iron (Fe)	7439-89-6		0.2576	mg
			Supplier	Copper (Cu)	7440-50-8		10.686	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0033	mg
Mold Compound-Black	19.21	mg		Epoxy resin	proprietary data		1.4408	mg
			Supplier	Phenolic Resin	Proprietary Data		0.4802	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		1.4408	mg
			Supplier	Carbon Black (C)	1333-86-4		0.096	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		15.7522	mg
Plating	0.12	mg	Supplier	Palladium (Pd)	7440-05-3		0.006	mg
			В	Nickel (Ni)	7440-02-0		0.108	mg
			Supplier	Gold (Au)	7440-57-5		0.006	mg
Wire Bond - Au	0.13	mg	Supplier	Gold (Au)	7440-57-5		0.13	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).