IPC ASSOCIATION CON	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under bo international and Pan-American copyright conventions.			nder both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.										
1752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi				rials and N	als and Mfg Information				
Supplier In	nformation														
Company name*			Company unique ID			1	Unique ID Authority				Respor	Response Date*			
onsemi											2024-0	2024-05-10			
Contact Name	e	Title - Contact]	Phone - Contact*				Email -	Email - Contact*				
Product-Env-	-Stewards	Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com				
Authorized Representative*			Title - Representative]	Phone - Representative*				Email -	Email - Representative*			
Product-Env-Stewards			Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
Re	Requester Item Number Mfr Item		Number Mfr Item Name				Effective Da	ite Ver	sion	Manufacturing Site		Weight*	UOM	Unit Type	
		NVMFS5C670NLWF Trench 6 60V NFET AFT3G		ET		2024-05-10		MY1			107.2528	mg	Each		
Manufactu	ring Proccess Informati	ion													
Ter	Terminal Plating / Grid Array Material Terminal Base Alloy			Alloy J.	-STD-020 MS	0 MSL Rating Peak Process Body Temperature Max Time at P			re Max Time at Pea	k Tempera	ture Numb	per of Reflow Cyc	les		
Matte Tin (Sn) - annealed CU Al			CU Alloy	Alloy 1			260 C		C	30	seco	nds 3			
Comments															
evel 1 - maxir	mum time at peak temperatui	re during sol	dering is 10-3	0 seconds											
or more info	ormation regarding material c	composition	please refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledges and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its paragraph. If the Company and the Supplier shall apply that agreement, will be the sole and exclusivesource of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted substance	s per the definition above except for selected exemp	tions Supplier Acceptance	* Accepted							
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.											
Supplier Digital Signature Ra	astislav Drska	-En									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Clip	13.512	mg	Supplier	Zinc (Zn)	7440-66-6		0.0162	mg
			Supplier	Iron (Fe)	7439-89-6		0.3175	mg
			Supplier	Copper (Cu)	7440-50-8		13.1742	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0041	mg
Die	0.727	mg	Supplier	Silicon (Si)	7440-21-3		0.727	mg
Die Attach Solder	1.4993	mg	Supplier	Silver (Ag)	7440-22-4		0.0375	mg
			A	Lead (Pb)	7439-92-1	7a	1.3869	mg
			Supplier	Tin (Sn)	7440-31-5		0.075	mg
Lead Frame	42.5398	mg	Supplier	Silver (Ag)	7440-22-4		0.0255	mg
			Supplier	Iron (Fe)	7439-89-6		0.0425	mg
			Supplier	Copper (Cu)	7440-50-8		42.459	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0128	mg
Mold Compound-Black	48.7198	mg		Epoxy resin	proprietary data		3.654	mg
			Supplier	Phenolic Resin	Proprietary Data		1.218	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		3.654	mg
			Supplier	Carbon Black (C)	1333-86-4		0.2436	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		39.9502	mg
Plating	0.2183	mg	Supplier	Tin (Sn)	7440-31-5		0.2183	mg
Wire Bond - Cu	0.0366	mg	Supplier	Copper (Cu)	7440-50-8		0.0366	mg