IPC ASSOCIATION ELECTRONICS	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			der both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lowe level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.								
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typhttp://www.ipc.org/IPC-175x Distribute				Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi				ials and Mfg Information				
upplier	Information													
Company name*			Company ur	Company unique ID			Unique ID Authority				Response Date*			
nsemi										2025-05-13				
Contact Na	nme	Title - Contact			I	Phone - Contact*				Email - Contact*				
Product-E	nv-Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com			
uthorized	Representative*	Title - Representative			I	Phone - Representative*				Email - Representative*				
Product-E	nv-Stewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
	Requester Item Number		Number	Mfr Item Name			Effective Date	Version	N	Manufacturing Site	V	/eight*	UOM	Unit Type
		1SMB5915BT3G ZEN SMB RE		ZEN SMB REG 3W	3 3W 3.9V TR		2025-05-13	25-05-13 CNP		1	14.91	mg	Each	
Ianufac	turing Process Inform	ation												
Terminal Plating / Grid Array Material Termina			erminal Base	minal Base Alloy J-STD-020 MSL Rating			Peak Process Body Temperature   Max Time at Peak				Temperature Number of Reflow Cycles			
I	Matte Tin (Sn) - annealed	C	CU Alloy	1			260		C	30	second	s <b>3</b>		
omments														
vel 1 - ma	ximum time at peak tempera	ture during sol	dering is 10-	30 seconds										
or more iı	nformation regarding materia	al composition	please refer t	o page 3										

RoHS Material Composition Declaration			Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU  RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledges and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier have provided as part of that agreement, will be the sole and exclusivesource of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale app										
RoHS Declaration * 4 - Item(s	) does not contain RoHS restricted substance	s per the definition above except for selected exemp	tions Supplier Acceptance	* Accepted						
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.										
Supplier Digital Signature Ra	astislav Drska	-En								

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

<b>Homogeneous Material</b>	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Clip	16.81	mg	Supplier	Zinc (Zn)	7440-66-6		0.0202	mg
			Supplier	Iron (Fe)	7439-89-6		0.395	mg
			Supplier	Copper (Cu)	7440-50-8		16.3897	mg
			Supplier	Phosphorus (P)	7723-14-0		0.005	mg
Die	0.7	mg	Supplier	Silicon (Si)	7440-21-3		0.7	mg
Die Attach Solder	0.52	mg	Supplier	Silver (Ag)	7440-22-4		0.013	mg
			A	Lead (Pb)	7439-92-1	7a	0.481	mg
			Supplier	Tin (Sn)	7440-31-5		0.026	mg
Lead Frame	46.99	mg	Supplier	Zinc (Zn)	7440-66-6		0.0564	mg
			Supplier	Iron (Fe)	7439-89-6		1.1043	mg
			Supplier	Copper (Cu)	7440-50-8		45.8153	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0141	mg
Mold Compound-Black	48.07	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		4.807	mg
			Supplier	Carbon Black (C)	1333-86-4		0.2403	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		6.9701	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		31.2455	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		4.807	mg
Plating	1.82	mg	Supplier	Tin (Sn)	7440-31-5		1.82	mg