Authorized Representative* Title - Representative Product-Env-Stewards Product Enviro Compliance NA Product-Env-Stewards	Pate*			
Company name* Company unique ID Unique ID Authority Response D 2024-05-18 Contact Name Title - Contact Product-Env-Stewards Authorized Representative* Product Enviro Compliance Title - Representative Product-Env-Stewards				
nsemi 2024-05-18 Contact Name Title - Contact Phone - Contact* Email - Cor Product-Env-Stewards Product Enviro Compliance NA Product-Enverted Representative* Phone - Representative* Email - Representative Phone - Representative* Product-Env-Stewards Product-Env-Stewards Product Enviro Compliance NA Product-Env-Stewards Product-Env-Stewards Product Enviro Compliance NA Product-Env-Stewards Product-Env-Stew				
Contact Name  Title - Contact  Product-Env-Stewards  Product Enviro Compliance  Authorized Representative*  Product-Env-Stewards  Product Enviro Compliance  Phone - Representative*  Phone - Representative*  Phone - Representative*  Product-Env-Stewards  Product Enviro Compliance  NA  Product-Env-Stewards  Product Enviro Compliance  NA  Product-Env-Stewards	ntact*			
Product-Env-Stewards       Product Enviro Compliance       NA       Product-Enverse         Authorized Representative*       Title - Representative       Phone - Representative*       Email - Representative*         Product-Env-Stewards       Product Enviro Compliance       NA       Product-Enversentative	ıtact*			
Authorized Representative* Title - Representative Product-Env-Stewards Product Enviro Compliance NA Product-Env-Stewards				
Product-Env-Stewards Product Enviro Compliance NA Product-En	Product-Env-Stewards@onsemi.com			
	Email - Representative*			
Requester Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Wei	Product-Env-Stewards@onsemi.com			
	ght* UOM Unit Type			
2SA2029M3T5G	mg Each			
Manufacturing Proccess Information  Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature	Number of Reflow Cycles			
Matter III (SII) - aimeaicu CC Anoy I 200 C 50 Seconds	3			
omments vel 1 - maximum time at peak temperature during soldering is 10-30 seconds				
or more information regarding material composition please refer to page 3				

RoHS Material Composition Declaration			Declaration Type *	Detail	led					
Directive 2015/863/EU amending RoHS Directive 2011/65/EU  RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier shave provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and/conditions of Sale applicable to such part shall apply.										
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substa	ances per the definition above	Supplier Ac	cceptance *	Accepted					
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructional Complete all of the required	fields on all neggs of this form. Calcut th		a duan dawn. This will display the signature on	a Digitally sign	the declaration (if recruired by the					
Instructions: Complete all of the required Requester) and click on Submit Form to			e drop-down. This will display the signature ar	ea. Digitally sign	the declaration (if required by the					

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.13	mg	Supplier	Silicon (Si)	7440-21-3		0.13	mg
Lead Frame	0.28		Supplier	Silver (Ag)	7440-22-4		0.0255	mg
			В	Nickel (Ni)	7440-02-0		0.103	mg
			Supplier	Iron (Fe)	7439-89-6		0.1414	mg
			Supplier	Copper (Cu)	7440-50-8		0.0101	mg
Mold Compound-Black	0.86		Supplier	Boron zinc hydroxide oxide	138265-88-0		0.0258	mg
			Supplier	Zinc Monoxide (ZnO)	1314-13-2		0.0043	mg
			Supplier	2,4,6-triamino-s-triazincompd.withs-triazine-triol	37640-57-6		0.0258	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.688	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0086	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		0.0688	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.0387	mg
Plating	0.003	mg	Supplier	Tin (Sn)	7440-31-5		0.003	mg
Wire Bond - Cu	0.002	mg	Supplier	Copper (Cu)	7440-50-8		0.002	mg