ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES*	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.												
752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					als and Mfg Information							
Supplier Informa	tion																
Company name*			Company unique ID			1	Unique ID Authority						Response Date*				
nsemi										2025-07-09							
Contact Name		Title - Contact]	Phone - Contact*					Email - Contact*						
Product-Env-Stewards			Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com					
Authorized Representative*			Title - Representative]	Phone - Representative*					Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com					
Requester	· · · · · · · · · · · · · · · · · · ·		m Number Mfr Item Name 3-1-TW30 Radio Transceiver				Effective Da	ate V	Version	Manufacturing Site		ng Site	Weight*		¢	UOM	Unit Type
							2025-07-09					5	54.89		mg	Each	
Ianufacturing P	roccess Information	1		1			1									1	1
Terminal Pl	Terminal Plating / Grid Array Material		erminal Base A	minal Base Alloy J-STD-020 M		L Rating	Peak Process		Body Temperature Max Time a		ne at Peak	ık Temperature Nun		Number of Reflow Cycles			
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)			CU Alloy 1		1		260		С		30		secon	is 3			
omments																	
vel 1 - maximum tim	ie at peak temperature d	luring sol	dering is 10-3	0 seconds													
or more information	regarding material com	position	please refer to	page 3													

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	3.28	mg	Supplier	Silicon (Si)	7440-21-3		3.28	mg
Die Attach	0.6	mg	Supplier	Epoxized Condensate Of Para- Hydrobenzaldehyde And Alkyl Phenol	129915-35-1		0.12	mg
			Supplier	Silver (Ag)	7440-22-4		0.48	mg
Lead Frame	26.96	mg	Supplier	Silver (Ag)	7440-22-4		0.5392	mg
			Supplier	Iron (Fe)	7439-89-6		0.5931	mg
			Supplier	Copper (Cu)	7440-50-8		25.8277	mg
Mold Compound-Black	22.31	mg		Epoxy Phenol Resin	proprietary data		2.3425	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		19.9674	mg
Plating	1.2	mg	Supplier	Palladium (Pd)	7440-05-3		0.0288	mg
			В	Nickel (Ni)	7440-02-0		1.056	mg
			Supplier	Gold (Au)	7440-57-5		0.1152	mg
Wire Bond - Au	0.54	mg	Supplier	Gold (Au)	7440-57-5		0.54	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).