ASSOCIATION CONNECTING	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.												
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					s Material	als and Mfg Information						
Supplier Informa	ation																
Company name*	Company unique ID				Unique ID Authority]	Response Date*						
onsemi													2024-04-28				
Contact Name	Title - Contact]	Phone - Contact*]	Email - Contact*						
Product-Env-Stewar	rds	Product Enviro Compliance				NA						Product-Env-Stewards@onsemi.com					
Authorized Represen	ntative*	Title - Representative]	Phone - Representative*]	Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance				NA						Product-Env-Stewards@onsemi.com				
Requester	Requester Item Number Mfr Iten		Number Mfr Item Name				Effective Date Version Manufacturing Site		g Site	W	'eight*	UON	N	Unit Type			
	CAT34C A		02HU4IGT4	24 2KB I2C SER EEPROM, SPD			2024-04-2	8		Т	ТНВ		1	.33	mg		Each
Manufacturing P	Proccess Information	l											·		·		
Terminal P	Terminal Plating / Grid Array Material		erminal Base Alloy J-STD-020 M		L Rating	Peak Pro		ss Body Temperature Max Time a		e at Peak T	t Peak Temperature		Number of Reflow Cycles				
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)		i) (no	CU Alloy 1		1		260		С		30 se		second	seconds 3			
Comments							· · ·							<u> </u>			
evel 1 - maximum tir	me at peak temperature d	luring sol	dering is 10-3	0 seconds													
or more information	n regarding material com	position	please refer to	page 3													

RoHS Material Composition Declaration				Declaration Type *	Detailed								
Directive 2015/863/EU amending RoHS Directive 2011/65/EU													
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of								
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted								
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all								
Exemption List Version	EL-2011/534/EU												
Declaration Signature													
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the								
Supplier Digital Signature Ra	stislav Drska	Le											

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.44	mg	Supplier	Silicon (Si)	7440-21-3		0.44	mg
Die Attach	0.25	mg	Supplier	Epoxized Condensate Of Para- Hydrobenzaldehyde And Alkyl Phenol	129915-35-1		0.05	mg
			Supplier	Silver (Ag)	7440-22-4		0.2	mg
Lead Frame	6.7	mg	Supplier	Tin (Sn)	7440-31-5		0.0167	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0147	mg
			Supplier	Chromium (Cr)	7440-47-3		0.0167	mg
			Supplier	Copper (Cu)	7440-50-8		6.6518	mg
Mold Compound-Black	3.8	mg		Epoxy resin	proprietary data		0.1786	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.38	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0038	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		3.059	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.1786	mg
Plating	0.08	mg	Supplier	Palladium (Pd)	7440-05-3		0.005	mg
			В	Nickel (Ni)	7440-02-0		0.0742	mg
			Supplier	Gold (Au)	7440-57-5		0.0009	mg
Wire Bond - Au	0.06	mg	Supplier	Gold (Au)	7440-57-5		0.06	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).