IPC ASSOCIATION CONNE	© Copyright 2005. I	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			der both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					ials and M	ials and Mfc Information			
upplier Info	ormation								,						
Company name*			Company unique ID			J	Unique ID Authority					Response Date*			
nsemi											2025-05-11				
Contact Name		Title - Contact			1	Phone - Contact*				Email - Contact*					
Product-Env-St	tewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
uthorized Repi	resentative*	Title - Representative			J	Phone - Representative*				Email - Representative*					
Product-Env-St	tewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
Requ	uester Item Number	Mfr Item	Number	Mfr Item Name			Effective Date	Version	n]	Manufacturing Site	,	Weight*	UOM	Unit Type	
		CAV24C08C4CTR 8KB I2C SER E		8KB I2C SER EEP	ROM	M 2025-0		-11			0.4682		mg	Each	
Ianufacturii	ng Proccess Informa	tion									·				
Terminal Plating / Grid Array Material T			Terminal Base Alloy J-STD-020 MSL		Rating	Peak Process Body Temper		Гетрегаtu	ture Max Time at Peak Tempe		ure Numb	er of Reflow Cyc	eles		
SnAgCu		C	CU Alloy 1				260		C	30	secon	ds 3			
omments															
vel 1 - maximu	ım time at peak temperatı	are during sol	dering is 10-3	30 seconds											
or more inform	nation regarding material	composition]	please refer t	o page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on informationprovided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.3895	mg	Supplier	Silicon (Si)	7440-21-3		0.3895	mg
Protection coat	0.0105	mg		Polyimide	proprietary data		0.0105	mg
RDL Sputter	4.0E-4	mg	Supplier	Titanium (Ti)	7440-32-6		0.0001	mg
			Supplier	Copper (Cu)	7440-50-8		0.0003	mg
Solder Ball	0.0523	mg	Supplier	Silver (Ag)	7440-22-4		0.0014	mg
			Supplier	Tin (Sn)	7440-31-5		0.0506	mg
			Supplier	Copper (Cu)	7440-50-8		0.0003	mg
UBM/RDL PCu	0.0153	mg	Supplier	Copper (Cu)	7440-50-8		0.0153	mg
UBM Sputter	2.0E-4	mg	Supplier	Titanium (Ti)	7440-32-6		0	mg
			Supplier	Copper (Cu)	7440-50-8		0.0002	mg