IPC ASSOCIATION CONNE	Material Comp © Copyright 2005. I international and Pa	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lowe level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
1752-21.1		IPC Web Site for Information on IPC-1752 Standard  Form Type http://www.ipc.org/IPC-175x  Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					erials and I	Mfg Informa	ition		
upplier Info	ormation				·										
Company name* Com				Company unique ID			Unique ID Authority				Respon	Response Date*			
onsemi											2025-0	2025-05-09			
Contact Name		Title - Contact			I	Phone - Contact*				Email	Email - Contact*				
Product-Env-St	tewards		Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
uthorized Rep	presentative*	Title - Representative			I	Phone - Representative*				Email	Email - Representative*				
Product-Env-Stewards Produ				roduct Enviro Compliance			NA				Produ	Product-Env-Stewards@onsemi.com			
Requ	uester Item Number	Mfr Item	Number	Mfr Item Name			Effective Dat	e Versio	on 1	Manufacturing Site		Weight*	UOM	Unit Type	
		CM1213A-04S7 4 CH. LOW CAPES		ESD		2025-05-09	CN1			7.1	mg	Each			
Ianufacturi	ing Proccess Informa	tion													
Terminal Plating / Grid Array Material T			Cerminal Base Alloy J-STD-020 MSI		SL Rating	Peak Process Body Temperat		Temperatu	ture Max Time at Peak Tempera		ature Num	ber of Reflow Cyc	eles		
Matte Tin (Sn) - annealed CU			U Alloy 1				260   C   30		seconds 3						
omments															
vel 1 - maximu	um time at peak temperat	ure during sol	dering is 10-3	30 seconds											
or more inforn	mation regarding material	composition	please refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	led						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU  RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substa	ances per the definition above	Supplier Ac	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructional Complete all of the required	fields on all neggs of this form. Calcut th		a duan dawn. This will display the signature on	a Digitally sign	the declaration (if recurined by the						
Instructions: Complete all of the required Requester) and click on Submit Form to			e drop-down. This will display the signature ar	ea. Digitally sign	the declaration (if required by the						

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Clip	3.51	mg	Supplier	Zinc (Zn)	7440-66-6		0.0042	mg
			Supplier	Iron (Fe)	7439-89-6		0.0842	mg
			Supplier	Copper (Cu)	7440-50-8		3.4187	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0028	mg
Die	0.2	mg	Supplier	Silicon (Si)	7440-21-3		0.2	mg
Die Attach	0.02	mg	Supplier	Silver (Ag)	7440-22-4		0.015	mg
			Supplier	Epoxy resins	129915-35-1		0.005	mg
Mold Compound-Black	3.32	mg		Epoxy Phenol Resin	proprietary data		0.3486	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		2.9714	mg
Plating	0.02	mg	Supplier	Tin (Sn)	7440-31-5		0.02	mg
Wire Bond - Au	0.03	mg	Supplier	Gold (Au)	7440-57-5		0.03	mg