IPC ASSOCIATION ELECTRONIC	© Copyright 200	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			nder both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
1752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typhttp://www.ipc.org/IPC-175x Distribute				k	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ials and Mfg Information			
upplie	r Information														
Company name* Company unique ID				ique ID		Unique ID Authority				Response Date*					
nsemi												2025-07-08			
Contact N	Jame		Title - Contact			1	Phone - Contact*				Email - Contact*				
Product-I	Env-Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
uthorize	ed Representative*	Title - Representative			1	Phone - Representative*				Email - Representative*					
Product-I	Env-Stewards	Product Env	Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com					
	Requester Item Number Mfr Iter		m Number Mfr Item Name				Effective Date Version		ersion	Manufacturing Site		V	/eight*	UOM	Unit Type
		ESD8006MUTAG Low cap ESD p		Low cap ESD pro	tection	2025-07-08						14.76		mg	Each
Ianufa	cturing Process Inform	mation										·		·	·
	erminal Plating / Grid Array Material		Terminal Base Alloy J-STD-02		J-STD-020 MSL	Rating	Peak Process Body Temperatur		re Max Time at Peak Temperature		re Num	ber of Reflow Cyc	cles		
Matte Tin (Sn) - annealed		CU Alloy 1			260 C		30 secon		second	s 3					
omments	3														
vel 1 - m	aximum time at peak temper	rature during so	ldering is 10-3	30 seconds											
or more	information regarding mater	rial composition	please refer t	o page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
cadmium, hexavalentchromium, polybromin contains a RoHS restricted substance inexce encompass all such components. Supplier cet as of the date that Supplier completes this Company acknowledges that Supplier may hindependently verified information provided certification in this paragraph. If the Compan	nated biphenyls and/or polybrominated diphess of an applicable quantity limit, please indriffes that it gathered the information it provom. Supplier acknowledges that Company wave relied on informationprovided by others of the supplier agrees that, at a minimusy and the Supplier enter into a written agree yesource of the Supplier's liability and the C	enyl ethers (each a "RoHS restricted substan licate below which, if any, RoHS exemption vides in this form using appropriate methods vill rely on this certification in determining the s in completing this form, and that Supplier um, itssuppliers have provided certifications ement with respect to the identified part, the tompany's remedies for issues that arise rega	s of the European Union member states) of the ce") in excess of the applicable quantity limit is you believe may apply. If the part is an assemb to ensure its accuracy and that such informatio e compliance of its products with European Ur may not have independently verified such infor regarding their contributions to the part, and the erms and conditions of that agreement, including information the Supplier provides in this	dentified above. If a ally with lower level in is true and correct tion member state la mation. However, in ose certifications are ag any warranty righ	homogeneous material within the part components, the declaration shall to the best of its knowledge and belief, was that implement the RoHS Directive. In situations where Supplier has not the at least as comprehensive as the lats and/or remedies provided as part of						
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level Substance		CAS Exempt		Weight	Unit of Measure
Die	0.98	mg	Supplier	Silicon (Si)	7440-21-3		0.98	mg
Die Attach	0.18		Supplier	Epoxized Condensate Of Para- Hydrobenzaldehyde And Alkyl Phenol	129915-35-1		0.036	mg
			Supplier	Silver (Ag)	7440-22-4		0.144	mg
Lead Frame	4.03		Supplier	Silver (Ag)	7440-22-4		0.0806	mg
			Supplier	Iron (Fe)	7439-89-6		0.0887	mg
			Supplier	Copper (Cu)	7440-50-8		3.8607	mg
Mold Compound-Black	8.09	mg		Epoxy Phenol Resin	proprietary data		0.7281	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		7.3619	mg
Plating	1.41	mg	Supplier	Tin (Sn)	7440-31-5		1.41	mg
Wire Bond	0.07	mg	Supplier	Palladium (Pd)	7440-05-3		0.0007	mg
			Supplier	Copper (Cu)	7440-50-8		0.0693	mg