ASEDCIATION CONNECTING ELECTRONICS INDUSTRIES® International and Pa	IPC Bannockh	ourn Illinois. A	Il rights reserved untions.	under both	This docume level parts, t	ent is a declarati the declaration e	on of the su	ibstances v s all lower	within the manufact level materials for	urer listed which the	item. Note: i manufacturer	f the item is an as has engineering	sembly with low responsibility.	
				Form Type Distribute	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Information									
upplier Information														
Company name* Com			Company unique ID			Unique ID Authority				Respo	Response Date*			
nsemi											2025-09-08			
ntact Name Title - Contact				Phone - Contact*				Email	Email - Contact*					
Product-Env-Stewards Product Envi			wiro Compliance			NA				Produ	Product-Env-Stewards@onsemi.com			
Authorized Representative* Title - Repre			presentative			Phone - Representative*				Email	Email - Representative*			
Product-Env-Stewards Produc			roduct Enviro Compliance			NA				Produ	Product-Env-Stewards@onsemi.com			
Requester Item Number	Mfr Item	Number	Mfr Item Name			Effective Date	e Date Version Manufacturing Site			Weight*	UOM	Unit Type		
	FAN486	FAN48615UC08X 3MHZ DC/DC Bo		oost 1.0A	ost 1.0A			P	РВВ		1.834591	mg	Each	
Ianufacturing Proccess Informa	ntion						-							
Terminal Plating / Grid Array M	laterial 7	rial Terminal Base Alloy		J-STD-020 MSI	-020 MSL Rating Pea		k Process Body Temperature Max Time at Peak		k Tempera	ature Numb	er of Reflow Cyd	eles		
SnAgCu CU Alloy		CU Alloy		1		260		С	30	seco	nds 3			
omments														
vel 1 - maximum time at peak temperat	ure during so	ldering is 10-3	0 seconds											
or more information regarding materia	l composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted						
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all						
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	stislav Drska	Le									

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

omogeneous Material Weight Unit of Measure L		Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Backside Protection Film	0.055211	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.0116	mg
			Supplier	Carbon Black (C)	1333-86-4		0.001	mg
			Supplier	Silica (SiO2)	14464-46-1		0.0311	mg
			Supplier	2,4,6-Tris[Bis(Methoxymethyl)Amino]- 1,3,5-Triazine	3089-11-0		0.0116	mg
Die	1.23125	mg	Supplier	Silicon (Si)	7440-21-3		1.2245	mg
			Supplier	Aluminum (Al)	7429-90-5		0.0067	mg
Solder Ball	0.547544	mg	Supplier	Silver (Ag)	7440-22-4		0.0309	mg
			Supplier	Tin (Sn)	7440-31-5		0.5133	mg
			Supplier	Copper (Cu)	7440-50-8		0.0033	mg
Under Bump Metal	5.86E-4	mg	Supplier	Titanium (Ti)	7440-32-6		0.0001	mg
			Supplier	Copper (Cu)	7440-50-8		0.0004	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).