ASSOCIATION CONNECTING LECTRONICS INDUSTRIES® international and	. IPC, Bannockt	ourn, Illinois. A	Ill rights reserved untions.	inder both	This docum level parts, t	ent is a declar he declaratio	ation of th	he substance asses all low	s within the manufact er level materials for	urer listed which the	item. Note: it manufacturer	f the item is an as has engineering	ssembly with lower responsibility.	
				Form Type * Distribute					rials and N	ials and Mfg Information				
Supplier Information														
Company name*	Company unique ID				Unique ID Authority					Response Date*				
onsemi									2025-0	2025-05-14				
Contact Name Title			Title - Contact			Phone - Contact*				Email	Email - Contact*			
Product-Env-Stewards Pr			Product Enviro Compliance			NA				Produ	Product-Env-Stewards@onsemi.com			
Authorized Representative* Ti			Title - Representative			Phone - Representative*			Email	Email - Representative*				
Product-Env-Stewards	Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com				
Requester Item Number	Mfr Item	Number Mfr Item Name			Effective Da	te Vers	ion	Manufacturing Site		Weight*	UOM	Unit Type		
	FSA1153	FSA1153UCX USB2.0 HS/AUD Switch with OVP		DIO/AUX DP3T	Analog	2025-05-14 PBB		PBB		2.416194	mg	Each		
Manufacturing Proccess Inform	ation													
Terminal Plating / Grid Array	Terminal Plating / Grid Array Material Terminal Ba		Alloy	J-STD-020 MSL	Rating	Peak Pr	ocess Bod	ly Temperati	re Max Time at Pea	k Tempera	ture Numb	er of Reflow Cy	cles	
SnAgCu CU Alloy			1		260		С	30	seco	nds 3				
Comments														
level 1 - maximum time at peak tempera	ature during so	ldering is 10-3	0 seconds											
For more information regarding materi	al composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted						
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all						
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	stislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight Unit of Measure Level Substance		Substance	CAS	Exempt	Weight	Unit of Measure	
Backside Protection Film	0.094382	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.0198	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0018	mg
			Supplier	Silica (SiO2)	14464-46-1		0.0531	mg
			Supplier	2,4,6-Tris[Bis(Methoxymethyl)Amino]- 1,3,5-Triazine	3089-11-0		0.0198	mg
Die	1.979882	mg	Supplier	Silicon (Si)	7440-21-3		1.9661	mg
			Supplier	Aluminum (Al)	7429-90-5		0.0138	mg
Solder Ball	0.341148	mg	Supplier	Silver (Ag)	7440-22-4		0.0193	mg
			Supplier	Tin (Sn)	7440-31-5		0.3198	mg
			Supplier	Copper (Cu)	7440-50-8		0.0021	mg
Under Bump Metal	7.82E-4	mg	Supplier	Titanium (Ti)	7440-32-6		0.0002	mg
			Supplier	Copper (Cu)	7440-50-8		0.0006	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).