ASSOCIATION CONNECT	© Copyright 2005. IPC,	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lowel level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Ty http://www.ipc.org/IPC-175x Distribut													
upplier Infor	rmation														
Company name*			Company unique ID			U	Unique ID Authority					Response Date*			
nsemi											2024-04	2024-04-20			
Contact Name	Title - Contact			Pl	Phone - Contact*					Email - Contact*					
Product-Env-Stev	wards	Product Enviro Compliance			N	NA				Produ	Product-Env-Stewards@onsemi.com				
uthorized Repre	esentative*	Title - Representative			Pl	Phone - Representative*				Email -	Email - Representative*				
Product-Env-Stev	wards	Product Enviro Compliance			N	NA				Produ	Product-Env-Stewards@onsemi.com				
Reques	ster Item Number	Mfr Item	em Number Mfr Item Name			E	Effective Date	Version	ion Manufacturing Site		te	Weight*		UOM	Unit Type
		FUSB302TV10M		X Automotive version of USB-C Port Control w/PD			2024-04-20 TH2			17.993 mg		mg	Each		
Ianufacturing	g Proccess Information	1					ļ			ļ					
Termina	rminal Plating / Grid Array Material		Terminal Base Alloy J-		J-STD-020 MSL Ratir	STD-020 MSL Rating		Peak Process Body Temperature		e Max Time at Peak Tempera		ture	re Number of Reflow Cycles		eles
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)		1) (no C	CU Alloy 1		1		260	С		30	seco	nds	3		
Comments											•				
vel 1 - maximum	ı time at peak temperature d	luring sol	dering is 10-3	0 seconds											
	tion regarding material con														

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU  RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	1.638	mg	Supplier	Silicon (Si)	7440-21-3		1.638	mg
Die Attach	0.22	mg	Supplier	Isobornyl Methacrylate	7534-94-3		0.0132	mg
			Supplier	Silver (Ag)	7440-22-4		0.1793	mg
			Supplier	Isobornyl Acrylate	5888-33-5		0.0132	mg
			Supplier	Misc.	Proprietary Data		0.0011	mg
			Supplier	Tricyclo[5.2.1.02,6]decanedimethanol Diacrylate (C18H24O4)	42594-17-2		0.0132	mg
Lead Frame	14.092	mg	Supplier	Zinc (Zn)	7440-66-6		0.0169	mg
			Supplier	Iron (Fe)	7439-89-6		0.3312	mg
			Supplier	Copper (Cu)	7440-50-8		13.7397	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0042	mg
Mold Compound-Black	1.543	mg	Supplier	Carbon Black (C)	1333-86-4		0.0077	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		1.3578	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		0.1003	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.0772	mg
Plating	0.103	mg	Supplier	Palladium (Pd)	7440-05-3		0.009	mg
			В	Nickel (Ni)	7440-02-0		0.092	mg
			Supplier	Gold (Au)	7440-57-5		0.002	mg
Wire Bond - Au	0.397	mg	Supplier	Gold (Au)	7440-57-5		0.397	mg