IPC ASSOCIATION CONNECTE ELECTRONICS INDUSTR	Material Comp © Copyright 2005. Il international and Par	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lowel level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.										
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ. http://www.ipc.org/IPC-175x Form Typ. Distribute				Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ials and Mfg Information					
Supplier Infor	mation															
Company name*			Company un	Company unique ID			Unique ID Authority					Response Date*				
nsemi												2024-04-24				
Contact Name		Title - Contact			F	Phone - Contact*					Email - Contact*					
Product-Env-Stev	wards	Product Enviro Compliance				NA NA					Product-Env-Stewards@onsemi.com					
authorized Repre	sentative*	Title - Representative			I	Phone - Representative*				Email - Representative*						
Product-Env-Stewards			Product Enviro Compliance			1	NA				Product-Env-Stewards@onsemi.com					
Reques	ster Item Number	FUSB302TVMPX Auto		em Number Mfr Item Name			Effective Da	te Version Ma		Manufacturing Site		V	Veight	<u></u> *	UOM	Unit Type
				Automotive versi w/ PD	Automotive version of USB-C Port Control w/ PD		2024-04-24 TH2		17.99		7.993		mg	Each		
/Ianufacturing	g Proccess Informat	tion														
Termina	al Plating / Grid Array Ma	nterial 7	Γerminal Base Alloy J-		J-STD-020 MSL R	20 MSL Rating		Peak Process Body Temperatur		re Max Time at Peak Temper		Temperatu	nture Number of Reflow Cycles		les	
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)			CU Alloy 1		1		260		С		30 seco		ls 3	3		
Comments																
evel 1 - maximum	ı time at peak temperatu	re during so	ldering is 10-3	30 seconds												
or more informa	tion regarding material	composition	please refer to	page 3												

RoHS Material Composition Declaration			Declaration Type *	Detail	led						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledges and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substa	ances per the definition above	Supplier Ac	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructional Complete all of the required	fields on all neggs of this form. Calcut th		a duan dawn. This will display the signature on	a Digitally sign	the declaration (if recurined by the						
Instructions: Complete all of the required Requester) and click on Submit Form to			e drop-down. This will display the signature ar	ea. Digitally sign	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	1.638	mg	Supplier	Silicon (Si)	7440-21-3		1.638	mg
Die Attach	0.22	mg	Supplier	Isobornyl Methacrylate	7534-94-3		0.0132	mg
			Supplier	Silver (Ag)	7440-22-4		0.1793	mg
			Supplier	Isobornyl Acrylate	5888-33-5		0.0132	mg
			Supplier	Misc.	Proprietary Data		0.0011	mg
			Supplier	Tricyclo[5.2.1.02,6]decanedimethanol Diacrylate (C18H24O4)	42594-17-2		0.0132	mg
Lead Frame	14.092	mg	Supplier	Zinc (Zn)	7440-66-6		0.0169	mg
			Supplier	Iron (Fe)	7439-89-6		0.3312	mg
			Supplier	Copper (Cu)	7440-50-8		13.7397	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0042	mg
Mold Compound-Black	1.543	mg	Supplier	Carbon Black (C)	1333-86-4		0.0077	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		1.3578	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		0.1003	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.0772	mg
Plating	0.103	mg	Supplier	Palladium (Pd)	7440-05-3		0.009	mg
			В	Nickel (Ni)	7440-02-0		0.092	mg
			Supplier	Gold (Au)	7440-57-5		0.002	mg
Wire Bond - Au	0.397	mg	Supplier	Gold (Au)	7440-57-5		0.397	mg