ABBOCIATION CONNECTING ELECTRONICS INDUSTRIES® MATERIAL COMPA	C, Bannockl	ourn, Illinois. A	ll rights reserved untions.	under both	This docume level parts, t	ent is a decla	ration of the second se	he substances asses all lowe	s within the er level ma	e manufacture terials for wh	er listed it	em. Note anufactur	: if the item i rer has engin	is an assemble ering response	ly with lower nsibility.
	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				e *	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials a					als and Mf	and Mfg Information			
Supplier Information															
Company name* Co			Company unique ID			Unique ID Authority					Response Date*				
onsemi										2025-07-12					
Contact Name Title			Title - Contact			Phone - Contact*					Email - Contact*				
Product-Env-Stewards Pr			Product Enviro Compliance			NA					Product-Env-Stewards@onsemi.com				
Authorized Representative*	Title - Representative			Phone - Representative*				Email - Representative*							
Product-Env-Stewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com						
Requester Item Number	Mfr Iten	n Number	Mfr Item Name			Effective Date Version Manufacturing		ring Site	Weight*		UOM	1	Unit Type		
	MC74H	MC74HC04ADTR2G LOG CMOS		S INVERTER HEX		2025-07-12	:		PH1		4	5.24	mg]	Each
Manufacturing Proccess Informat	ion		1					ļ					I		
Terminal Plating / Grid Array Ma	terial	Ferminal Base A	Alloy	J-STD-020 MSL Rating		Peak Process Body Te		ly Temperatu	erature Max Time at Peak T		Temperature Number of R		nber of Refle	ow Cycles	
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)		CU Alloy 1		1		260		С	30 s		second	seconds 3			
Comments															
evel 1 - maximum time at peak temperatu	re during so	ldering is 10-3	0 seconds												
or more information regarding material	composition	please refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth					
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of				
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted				
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all				
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.									
Supplier Digital Signature Ra	stislav Drska	Le							

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	2.0	mg	Supplier	Silicon (Si)	7440-21-3		2	mg	
Die Attach	1.44	mg		Epoxy resin	proprietary data		0.144	mg	
			Supplier	Silver (Ag)	7440-22-4		1.152	mg	
			Supplier	Formaldehyde Polymer	9003-36-5		0.144	mg	
Lead Frame 22.	22.54	mg	Supplier	Iron (Fe)	7439-89-6		0.4283	mg	
			Supplier	Copper (Cu)	7440-50-8		22.1117	mg	
Mold Compound-Black 19	19.0	mg		Epoxy resin	proprietary data		0.95	mg	
			Supplier	Phenolic Resin	Proprietary Data		0.38	mg	
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.475	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.095	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		17.1	mg	
Plating	0.04	mg	Supplier	Palladium (Pd)	7440-05-3		0.003	mg	
			В	Nickel (Ni)	7440-02-0		0.0364	mg	
			Supplier	Gold (Au)	7440-57-5		0.0006	mg	
Wire Bond - Cu	0.22	mg	Supplier	Copper (Cu)	7440-50-8		0.22	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).