ASDCIATION CONNECTING ELECTRONICS INDUSTRIES® INCLUSTRIES	PC. Bannockl	burn. Illinois. A	Il rights reserved untions.	under both	This docume level parts, t	ent is a declara he declaration	ion of the s encompasse	ubstances es all lowe	within the r level mat	manufacture erials for wh	er listed ite nich the ma	m. Note: nufacture	if the item is an as r has engineering	sembly with low responsibility.
	IPC Web Site for Information on IPC-1752 Standard Form http://www.ipc.org/IPC-175x Disc				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Info					Informat	tion			
Supplier Information														
Company name* Compa			ompany unique ID			Unique ID Authority					Response Date*			
semi											2024-05-16			
Contact Name	tact Name Title - Contact				Phone - Contact*				Email - Contact*					
Product-Env-Stewards Product Env			Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Authorized Representative* Title - Repres			esentative			Phone - Representative*				Email - Representative*				
Product-Env-Stewards Product Er			uct Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Requester Item Number	Mfr Iten	n Number	Mfr Item Name			Effective Dat	e Version	n Manufacturing Site		ring Site	W	eight*	UOM	Unit Type
	MC7905	5CD2TR4G	ANA 1A 5V NEGATIVE VREG		ì	2024-05-16		1	MY1		90	9.21	mg	Each
Manufacturing Proccess Informa	tion										İ		·	
Terminal Plating / Grid Array M	aterial 7	Ferminal Base	Alloy	J-STD-020 MSL Rating		Peak Pro	Process Body Temperature Max Time		me at Peak	ak Temperature Number of		ber of Reflow Cyc	les	
Matte Tin (Sn) - annealed CU Alloy		CU Alloy		1		260		С	30		second	3		
omments														
vel 1 - maximum time at peak temperat	ire during so	ldering is 10-3	0 seconds											
or more information regarding material	composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted						
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).								
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required Requester) and click on Submit Form to h			e drop-dowi	a. This will display the signature area. Digita	lly sign the declaration (if required by the						
Supplier Digital Signature	astislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.19	mg	Supplier	Silicon (Si)	7440-21-3		0.19	mg
Die Attach	11.31	mg	А	Lead (Pb)	7439-92-1	7a	10.7445	mg
			Supplier	Tin (Sn)	7440-31-5		0.5655	mg
Lead Frame	340.51	mg	В	Nickel (Ni)	7440-02-0		1.0215	mg
			Supplier	Copper (Cu)	7440-50-8		339.4885	mg
Mold Compound-Black	529.31	mg		Epoxy resin	proprietary data		26.4655	mg
			Supplier	Phenolic Resin	Proprietary Data		26.4655	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		10.5862	mg
			Supplier	Carbon Black (C)	1333-86-4		2.6465	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		463.1462	mg
Plating	27.15	mg	Supplier	Tin (Sn)	7440-31-5		27.15	mg
Wire Bond - Cu	0.74	mg	Supplier	Copper (Cu)	7440-50-8		0.74	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signar range of distribution unless otherwise noted)