©	<b>Iaterial Composit</b> Copyright 2005. IPC, 1 ternational and Pan-An	Bannockbi	urn, Illinois. A	ll rights reserved untions.	under both	This docum level parts, t	ent is a declara he declaration	ion of the s encompasse	ubstances es all lower	within the manufactur r level materials for w	rer listed i which the r	item. Note: i nanufacturer	f the item is an as r has engineering	ssembly with lower responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				e *	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information				
Supplier Informatio	n														
Company name*			Company unique ID				Unique ID Authority					Response Date*			
onsemi											2025-06-04				
Contact Name			Title - Contact				Phone - Contact*				Email - Contact*				
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Authorized Representative*			Title - Representative				Phone - Representative*			Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Requester Iter	Requester Item Number Mfr Item		n Number Mfr Item Name				Effective Dat	e Version	Ν	Manufacturing Site		Weight*	UOM	Unit Type	
		MMSZ4679T1G ZI		ZEN SOD123 REG 0.5W 2.0V			2025-06-04	4 CN1			11.67	mg	Each		
Manufacturing Pro	ccess Information	ı –									· · · ·				
Terminal Plating / Grid Array Material Termin		erminal Base A	Il Base Alloy J-STD-020 MSL		L Rating	Peak Pro	Peak Process Body Temperature M		e Max Time at Peak	Tempera	ture Numb	per of Reflow Cy	cles		
Matte Tin (Sn) - annealed CU			J Alloy 1			260 C 30		30	seconds 3						
Comments															
evel 1 - maximum time a	at peak temperature d	uring sole	dering is 10-3	0 seconds											
For more information re	garding material com	position p	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth					
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of				
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted					
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all				
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.									
Supplier Digital Signature Ra	stislav Drska	Le							

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	0.88	mg	Supplier	Silicon (Si)	7440-21-3		0.88	mg	
Lead Frame	3.19	mg	В	Nickel (Ni)	7440-02-0		1.158	mg	
			Supplier	Iron (Fe)	7439-89-6		1.6014	mg	
			Supplier	Copper (Cu)	7440-50-8		0.4306	mg	
Mold Compound-Black	6.51	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.651	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.0325	mg	
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		0.9439	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		4.2315	mg	
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.651	mg	
Plating	0.8	mg	Supplier	Tin (Sn)	7440-31-5		0.8	mg	
Wire Bond	0.29	mg	Supplier	Palladium (Pd)	7440-05-3		0.0038	mg	
			Supplier	Copper (Cu)	7440-50-8		0.2862	mg	