	CONNECTING CS INDUSTRIES® International and Pan	<b>Osition Dec</b> PC, Bannockb -American co	c <b>laration</b> ourn, Illinois. A pyright conve	Il rights reserved untions.	nder both	This docume level parts, t	ent is a declara he declara	ation of encon	f the substances npasses all low	within the reaction of the second sec	manufactur erials for wh	er listed it hich the m	em. Note: i anufacture	if the item is an as r has engineering	sembly with lower responsibility.	
1752-21.1					Form Type Distribute	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ous Materia	als and Mfg Information				
Supplie	r Information															
Company name* Comp				Company unique ID			Unique ID Authority					Response Date*				
onsemi												2025-06-07				
Contact N	lame		Title - Contact				Phone - Contact*					Email - Contact*				
Product-l	Env-Stewards		Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com				
uthorize	ed Representative*		Title - Representative				Phone - Representative*				Email - Representative*					
Product-	Env-Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
	Requester Item Number Mfr Item Nu   MUR1100E		n Number Mfr Item Name				Effective Dat	ate Version Manufacturing Sit		ing Site	V	Veight*	UOM	Unit Type		
			00EG	G REC SURM 1A 1KV ULTFST			2025-06-07 CNP			250.99		mg	Each			
/Ianufa	cturing Proccess Informat	ion														
	Terminal Plating / Grid Array Material		Terminal Base Alloy J-STD-020 M		-STD-020 MSI	L Rating	Peak Process Body Temperat		ure Max Time at Peak Temp		Temperate	ire Num	ber of Reflow Cyc	les		
	Matte Tin (Sn) - annealed		CU Alloy NA			0 C		30		second	ls 3					
omments	3															
or more	information regarding material of	composition	please refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 4 - Item(	s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted						
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).								
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required Requester) and click on Submit Form to h			e drop-dowi	a. This will display the signature area. Digita	lly sign the declaration (if required by the						
Supplier Digital Signature	astislav Drska	Le									

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.18	mg	Supplier	Silicon (Si)	7440-21-3		0.18	mg
Die Attach Solder	7.98	mg	Supplier	Silver (Ag)	7440-22-4		0.1995	mg
			А	Lead (Pb)	7439-92-1	7a	7.3815	mg
			Supplier	Tin (Sn)	7440-31-5		0.399	mg
Lead Frame	125.08	mg	В	Nickel (Ni)	7440-02-0		0.2502	mg
			Supplier	Copper (Cu)	7440-50-8		124.8298	mg
Mold Compound-Black	116.8	mg		Metal Hydroxide	proprietary data		5.84	mg
			Supplier	Carbon Black (C)	1333-86-4		1.168	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		87.6	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		11.68	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		10.512	mg
Plating	0.95	mg	Supplier	Tin (Sn)	7440-31-5		0.95	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3