ASSOCIATION CONNECT	© Copyright 2005, IPC	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.										
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute										Mfg In	formatio	1		
Supplier Infor	mation								·	U						
Company name*		Company unique ID			Ţ	Unique ID Authority					Response Date*					
nsemi													2024-05-11			
Contact Name		Title - Contact			I	Phone - Contact*				Email	Email - Contact*					
Product-Env-Stev	wards	Product Enviro Compliance				NA				Prod	Product-Env-Stewards@onsemi.com					
uthorized Repre	esentative*	Title - Representative			I	Phone - Representative*				Email	Email - Representative*					
Product-Env-Stev	wards	Product Enviro Compliance				NA				Prod	Product-Env-Stewards@onsemi.com					
Reques	ster Item Number	Mfr Item	em Number Mfr Item Name				Effective Dat	e Versio	on N	Manufacturing Site		Weight*		UOM	Unit Type	
		NC7SP17FHX ULP 1 Buffer		ULP 1 Buffer Sc			2024-05-11 TH		ГН2		1.397 mg		Each			
Ianufacturing	g Proccess Informatio	n		,				1								
Termina	al Plating / Grid Array Material		Terminal Base Alloy		J-STD-020 M	D-020 MSL Rating		Peak Process Body Temperat		re Max Time at Peak Temper		rature	ature Number of Reflow Cycles		eles	
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)		u) (no	CU Alloy		1		260		С	30	seco		3			
Comments																
vel 1 - maximum	n time at peak temperature	during sol	ldering is 10-3	0 seconds												
or more informa	ntion regarding material co	nposition	please refer to	page 3												

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU  RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier has not orditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty r											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.111	mg	Supplier	Silicon (Si)	7440-21-3		0.111	mg
Die Attach Epoxy	0.014	mg		Epoxy resin	proprietary data		0.0091	mg
			Supplier	Aluminum Trioxide (Al2O3)	1344-28-1		0.0049	mg
Lead Frame	0.402	mg	Supplier	Zinc (Zn)	7440-66-6		0.0005	mg
			Supplier	Iron (Fe)	7439-89-6		0.0094	mg
			Supplier	Copper (Cu)	7440-50-8		0.392	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0001	mg
Mold Compound-Black	0.852	mg	Supplier	Carbon Black (C)	1333-86-4		0.0043	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		0.7498	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		0.0554	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.0426	mg
Plating	0.014		Supplier	Palladium (Pd)	7440-05-3		0.001	mg
			В	Nickel (Ni)	7440-02-0		0.013	mg
			Supplier	Gold (Au)	7440-57-5		0	mg
Wire Bond - Au	0.004	mg	Supplier	Gold (Au)	7440-57-5		0.004	mg