IPC ASSOCIATION CONNECTED INDU	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			der both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				Declaration Class * Class 6 - RoHS Yes/No. Homogeneous Mater					ials and Mfg Information				
upplier Inf	formation														
Company name	e*	Company unique ID			J	Unique ID Authority				Response Date*					
nsemi											2024-04-23				
Contact Name		Title - Contact			I	Phone - Contact*				Email - Contact*					
Product-Env-Stewards			Product Enviro Compliance]	NA				Product-Env-Stewards@onsemi.com				
uthorized Rej	presentative*	Title - Representative			I	Phone - Representative*				Email - Representative*					
Product-Env-S	Stewards	Product Enviro Compliance			1	NA				Product-Env-Stewards@onsemi.com					
Req	quester Item Number	Mfr Item	Number	Mfr Item Name			Effective Date	Version	N	Manufacturing Site		ght*	UOM	Unit Type	
		NCP1013ST65T3G ANA FXD FRI		ANA FXD FREQ 7	700V MOSFET 20		2024-04-23 MY1		MY1 109.99		99	mg	Each		
Ianufactur	ring Proccess Informa	ation											·		
2 ,			erminal Base	minal Base Alloy J-STD-020 MSL Rating			Peak Process Body Temperature Max Time at Peak				Temperature Number of Reflow Cycles				
Mat	tte Tin (Sn) - annealed	C	CU Alloy	1			260		C	30	seconds	3			
omments															
vel 1 - maxim	num time at peak temperat	ture during sol	dering is 10-3	30 seconds											
or more infor	mation regarding materia	l composition	please refer t	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on informationprovided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	3.3	mg	Supplier	Silicon (Si)	7440-21-3		3.3	mg
Die Attach	2.37	mg	Supplier	Silver (Ag)	7440-22-4		1.7775	mg
			Supplier	Epoxy resins	129915-35-1		0.5925	mg
Lead Frame	37.17		Supplier	Silver (Ag)	7440-22-4		0.4832	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0372	mg
			Supplier	Iron (Fe)	7439-89-6		0.8921	mg
			Supplier	Copper (Cu)	7440-50-8		35.7575	mg
Mold Compound-Black	59.7			Epoxy resin	proprietary data		2.985	mg
			Supplier	Phenolic Resin	Proprietary Data		2.985	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		1.194	mg
			Supplier	Carbon Black (C)	1333-86-4		0.2985	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		52.2375	mg
Plating	7.44	mg	Supplier	Tin (Sn)	7440-31-5		7.44	mg
Wire Bond - Au	0.01	mg	Supplier	Gold (Au)	7440-57-5		0.01	mg