	© Convright 2005 IPC Bannockburn Illinois All rights reserved under both					This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.										
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ials and M	als and Mfg Information					
Supplier Info	rmation															
Company name*			Company unique ID			Unique ID Authority					Respon	Response Date*				
onsemi											2025-06	2025-06-05				
Contact Name		Title - Contact				Phone - Contact*					Email -	Email - Contact*				
Product-Env-Ste	Product-Env-Stewards			Product Enviro Compliance			NA					Product-Env-Stewards@onsemi.com				
Authorized Representative*			Title - Representative			Phone - Representative*					Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance			NA					Product-Env-Stewards@onsemi.com					
Reque	Requester Item Number Mfr Item			Number Mfr Item Name			Effective I	Date V	rsion	Manufacturing Site			Weight	t*	UOM	Unit Type
		FEATUR			JASI-RESONANT CONTROLLER RING VALLEY LOCKOUT HING		2025-06-0	5		PH1			73.3		mg	Each
Manufacturin	ng Proccess Information	1														
Terminal Plating / Grid Array Material Termin			erminal Base A	ninal Base Alloy J-STD-020 MSL Rating		Rating	Peak Process Body Temperature Max		ax Time at Peak	ak Temperature		Number o	f Reflow Cycl	es		
Matte Tin (Sn) - annealed CU Alloy 1			1		260		С	30)	secor	nds 3	3				
Comments																
level 1 - maximur	m time at peak temperature d	uring sol	dering is 10-3	0 seconds												
For more inform	ation regarding material com	position j	please refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU												
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of							
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted							
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all							
Exemption List Version	EL-2011/534/EU											
Declaration Signature												
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the							
Supplier Digital Signature Ra	stislav Drska	Le										

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	1.1	mg	Supplier	Silicon (Si)	7440-21-3		1.1	mg
Die Attach Epoxy	0.1	mg		Epoxy resin	proprietary data		0.065	mg
			Supplier	Aluminum Trioxide (Al2O3)	1344-28-1		0.035	mg
Lead Frame	24.0	mg	Supplier	Silver (Ag)	7440-22-4		0.1608	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0288	mg
			Supplier	Iron (Fe)	7439-89-6		0.564	mg
			Supplier	Copper (Cu)	7440-50-8		23.2392	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0072	mg
Mold Compound-Black	46.9	mg		Epoxy resin	proprietary data		2.345	mg
			Supplier	Phenolic Resin	Proprietary Data		0.938	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		1.1725	mg
			Supplier	Carbon Black (C)	1333-86-4		0.2345	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		42.21	mg
Plating	0.9	mg	Supplier	Tin (Sn)	7440-31-5		0.9	mg
Wire Bond	0.3	mg	Supplier	Palladium (Pd)	7440-05-3		0.0075	mg
			Supplier	Gold (Au)	7440-57-5		0.003	mg
			Supplier	Copper (Cu)	7440-50-8		0.2895	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).