	Material Composit Copyright 2005. IPC, F nternational and Pan-Am	Bannockbi	urn, Illinois. A	ll rights reserved untions.	under both le	This docume evel parts, t	ent is a decl he declarati	aration ion enc	of the substanc ompasses all lov	es within wer level	the manufactu materials for v	rer listed i which the r	tem. Note nanufactu	e: if the it arer has e	tem is an assen ngineering res	mbly with lowe ponsibility.
					Form Type * Distribute						ials and Mfg Information					
Supplier Informati	on															
Company name*			Company unique ID			Unique ID Authority					Respon	Response Date*				
onsemi												2025-05	2025-05-11			
Contact Name			Title - Contact			Phone - Contact*					Email -	Email - Contact*				
Product-Env-Stewards			Product Enviro Compliance			NA					Produc	Product-Env-Stewards@onsemi.com				
Authorized Representative*			Title - Representative			Phone - Representative*				Email -	Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance			NA				Produc	Product-Env-Stewards@onsemi.com					
Requester Item Number Mfr Item		Mfr Item	Number Mfr Item Name				Effective I	Date	Version	Manufacturing Site			Weight*	U	JOM	Unit Type
		NCP1616A1DR2G High Voltage Hig Correction Contro		gh Efficiency Pow oller	er Factor	2025-05-11 PH1			76.13		n	ng	Each			
Manufacturing Pro	occess Information	L														
Terminal Plating / Grid Array Material Terminal B			erminal Base A	Alloy	J-STD-020 MSL	Rating	Peak	Process	Body Tempera	ture Ma	x Time at Peal	Tempera	ture Nu	mber of I	Reflow Cycle:	5
Matte Tin (Sn) - annealed CU Alloy			1		260		С	30		secor	nds 3					
Comments																
level 1 - maximum time	at peak temperature d	uring sole	dering is 10-3	0 seconds												
For more information r	egarding material com	position p	please refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed								
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	irective 2011/65/EU (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DBP).												
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of								
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted								
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all								
Exemption List Version	EL-2011/534/EU												
Declaration Signature													
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the								
Supplier Digital Signature Ra	stislav Drska	Le											

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	2.62	mg	Supplier	Silicon (Si)	7440-21-3		2.62	mg	
Die Attach	0.39	mg	Supplier	Epoxized Condensate Of Para- Hydrobenzaldehyde And Alkyl Phenol	129915-35-1		0.078	mg	
			Supplier	Silver (Ag)	7440-22-4		0.312	mg	
Lead Frame	21.32	mg	Supplier	Silver (Ag)	7440-22-4		0.3624	mg	
			Supplier	Zinc (Zn)	7440-66-6		0.0256	mg	
			Supplier	Iron (Fe)	7439-89-6		0.501	mg	
			Supplier	Copper (Cu)	7440-50-8		20.4246	mg	
			Supplier	Phosphorus (P)	7723-14-0		0.0064	mg	
Mold Compound-Black	50.28	mg		Epoxy Phenol Resin	proprietary data		5.2794	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		45.0006	mg	
Plating	1.37	mg	Supplier	Tin (Sn)	7440-31-5		1.37	mg	
Wire Bond - Au	0.15	mg	Supplier	Gold (Au)	7440-57-5		0.15	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).