© Copyri	ial Composition ight 2005. IPC, Bann onal and Pan-America	ockburn, Illinois. A	Il rights reserved nations.	under both	This docume level parts, th	ent is a declarati he declaration e	on of the su	ibstances v s all lower	vithin the manufactu level materials for v	rer listed it which the m	em. Note: anufacture	if the item is an as r has engineering	sembly with low responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				*	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information			
upplier Information														
Company name* C			Company unique ID			Unique ID Authority				Respons	Response Date*			
onsemi										2025-07-	2025-07-05			
Contact Name Title - Cont			ontact			Phone - Contact*				Email - (	Email - Contact*			
Product-Env-Stewards Product			roduct Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Authorized Representative* Title - H			tle - Representative			Phone - Representative*			Email - Representative*					
Product-Env-Stewards Pr			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Requester Item Num	Requester Item Number Mfr Iten		n Number Mfr Item Name			Effective Date	Version	on Manufacturing Site		V	Veight*	UOM	Unit Type	
	NCF	NCP605MN28T2G 500MA AC		ACMOS LDO		2025-07-05		М	MY1		3.32	mg	Each	
Ianufacturing Proccess	Information						1					I		
Terminal Plating / Gri	Terminal Plating / Grid Array Material Terminal Base A		Alloy	J-STD-020 MSL Rating			Peak Process Body Temperature Max Time at Peak			Temperature Number of Reflow Cycles				
Matte Tin (Sn) - annealed CU A		CU Alloy	1			260 C 30		30	seconds 3					
omments														
vel 1 - maximum time at peak	k temperature durin	g soldering is 10-3	0 seconds											
or more information regardin	ng material composit	ion please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Disobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted							
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all						
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	stislav Drska	Le									

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	0.99	mg	Supplier	Silicon (Si)	7440-21-3		0.99	mg	
Die Attach	0.24	mg	Supplier	Epoxized Condensate Of Para- Hydrobenzaldehyde And Alkyl Phenol	129915-35-1		0.0768	mg	
			Supplier	Aluminum Trioxide (Al2O3)	1344-28-1		0.1632	mg	
Lead Frame	5.86	mg	Supplier	Silver (Ag)	7440-22-4		0.1172	mg	
			Supplier	Iron (Fe)	7439-89-6		0.1289	mg	
			Supplier	Copper (Cu)	7440-50-8		5.6139	mg	
Mold Compound-Black	14.8	mg		Epoxy Phenol Resin	proprietary data		1.332	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		13.468	mg	
Plating	1.22	mg	Supplier	Tin (Sn)	7440-31-5		1.22	mg	
Wire Bond - Au	0.21	mg	Supplier	Gold (Au)	7440-57-5		0.21	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted)