ASSOCIATION CONNECTIN	Material Composi © Copyright 2005. IPC, international and Pan-Ar	Bannockb	urn, Illinois. A	ll rights reserved untions.	nder both	This docume level parts, t	ent is a declaration e	ion of the su encompasses	ibstances s s all lower	within the manufactur level materials for w	er listed i hich the n	tem. Note: i nanufacturer	f the item is an as r has engineering	sembly with lower responsibility.	
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				e *	 Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi 					als and Mfg Information				
Supplier Inform	ation														
Company name*			Company unique ID				Unique ID Authority					Response Date*			
onsemi											2025-06-06				
Contact Name			Title - Contact				Phone - Contact*				Email - Contact*				
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Authorized Representative*			Title - Representative				Phone - Representative*			Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Requeste	Requester Item Number Mfr Item		n Number Mfr Item Name				Effective Date	Version	Ν	Ianufacturing Site		Weight*	UOM	Unit Type	
		NCV459MNWTBG 4		4A Single Load Switch			2025-06-06		N	MY1		26.8	mg	Each	
Manufacturing	Proccess Information	1													
Terminal Plating / Grid Array Material Termi			erminal Base A	minal Base Alloy J-STD-020 MSL		L Rating	Peak Process Body Temperature M		e Max Time at Peak	Temperat	ure Numb	per of Reflow Cyc	les		
Matte Tin (Sn) - annealed CU Alloy			CU Alloy		1		260		С	30	secon	ds 3			
Comments															
evel 1 - maximum t	ime at peak temperature o	luring sol	dering is 10-3	0 seconds											
or more information	on regarding material con	position	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth					
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of				
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted					
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.									
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.									
Supplier Digital Signature Ra	stislav Drska	Le							

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure		
Die	1.38	mg	Supplier	Silicon (Si)	7440-21-3		1.38	mg		
Die Attach	0.14	mg	Supplier	Epoxized Condensate Of Para- Hydrobenzaldehyde And Alkyl Phenol	129915-35-1		0.028	mg		
			Supplier	Silver (Ag)	7440-22-4		0.112	mg		
Lead Frame	10.18	mg	Supplier	Silver (Ag)	7440-22-4		0.0814	mg		
			Supplier	Zinc (Zn)	7440-66-6		0.0102	mg		
			Supplier	Iron (Fe)	7439-89-6		0.2647	mg		
			Supplier	Copper (Cu)	7440-50-8		9.8237	mg		
Mold Compound-Black	14.23	mg	Supplier	Epoxy resins	129915-35-1		0.7115	mg		
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.7115	mg		
			Supplier	Carbon Black (C)	1333-86-4		0.0569	mg		
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		0.3273	mg		
			Supplier	Fused Silica (SiO2)	60676-86-0		12.0955	mg		
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.3273	mg		
Plating	0.68	mg	Supplier	Tin (Sn)	7440-31-5		0.68	mg		
Wire Bond - Au	0.19	mg	Supplier	Gold (Au)	7440-57-5		0.19	mg		

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).