ASSOCIATION CONNECTI ELECTRONICS INDUSTRI	Material Compo © Copyright 2005. IP international and Pan-	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lowe level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				e *	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					ials and Mfg Information			
upplier Inform	nation				·		<u> </u>								
Company name*			Company unique ID			J	Unique ID Authority					Response Date*			
nsemi											2025-07-05				
Contact Name			Title - Contact			I	Phone - Contact*				Email - Contact*				
Product-Env-Stew	ards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
uthorized Repres	entative*	Title - Representative			I	Phone - Representative*				Email - Representative*					
Product-Env-Stew	ards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
Reques	Requester Item Number Mfr Iter		m Number Mfr Item Name				Effective Date	e Versio	n l	Manufacturing Site	,	Weight*	UOM	Unit Type	
		NCV7321MW2R2G ESD IMPROVED		LIN TRANS	C.	2025-07-05	PHG			23.0	mg	Each			
Ianufacturing	Process Informat	ion											·		
Terminal Plating / Grid Array Material			Terminal Base Alloy J-STD-020 MS		SL Rating	Peak Process Body Temperatu		re Max Time at Peak	Temperat	ure Numb	per of Reflow Cyc	eles			
Matte Tin (Sn) - annealed			CU Alloy 1				260 C 30			seconds 3					
omments															
vel 1 - maximum	time at peak temperatui	re during sol	dering is 10-3	30 seconds											
or more informat	ion regarding material o	composition	please refer t	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed					
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.										
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted					
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the					

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	1.904	mg	Supplier	Silicon (Si)	7440-21-3		1.904	mg
Die Attach	0.062	mg	Supplier	Silver (Ag)	7440-22-4		0.0527	mg
			Supplier	Acrylic resins	Proprietary Data		0.0093	mg
Lead Frame	6.595		Supplier	Tin (Sn)	7440-31-5		0.0165	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0145	mg
			Supplier	Chromium (Cr)	7440-47-3		0.0165	mg
			Supplier	Copper (Cu)	7440-50-8		6.5475	mg
Lead Frame plating	0.135	mg	Supplier	Silver (Ag)	7440-22-4		0.135	mg
Mold Compound-Black	13.208	mg	Supplier	Silica Amorphous (SiO2)	7631-86-9		1.0566	mg
			Supplier	Carbon Black (C)	1333-86-4		0.066	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		0.2642	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		10.3683	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		1.0566	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.3962	mg
Plating	0.884	mg	Supplier	Tin (Sn)	7440-31-5		0.884	mg
Wire Bond - Au	0.212	mg	Supplier	Gold (Au)	7440-57-5		0.212	mg