Contact Name Title - Contact Phone - Contact* Product-Env-Stewards Authorized Representative* Product-Env-Stewards Product Enviro Compliance Title - Representative Phone - Representative* Product-Env-Stewards Product-Env-Stewards Product-Enviro Compliance NA Product-Env-Stewards@onsemi.com Requester Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight* UOM Uniter Stewards Weight*	ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.		der both This docum- level parts, t	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with le level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
Company name* Company name* Company name* Company name* Contact Name Contact Name Title - Contact Product Enviro Compliance NA Product Enviro Stewards Onsemi.com  NA Product Enviro Stewards Onsemi.com  NA NRVTSAF360T3G 60V 3A Trench Rectifier in SMAFL package 2025-06-07 MY1 83.64 mg Eac  Manufacturing Proccess Information  Manufacturing Proccess Information  Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles Matte Tin (Sn) - annealed Comments	752-21.1										als and Mfg	Informatio	n	
Insemi In	upplier Inform	ation												
Title - Contact Name Product Env-Stewards Uthorized Representative* Product Env-Stewards Product Enviro Compliance Product Enviro Compliance Product Enviro Compliance Product Enviro Compliance Product Env-Stewards Product Enviro Compliance NA Product-Env-Stewards Product-Env-Stewar	Company name*			Company unique ID			Unique ID Authority				Response Date*			
Product Env-Stewards Authorized Representative* Title - Representative Product Enviro Compliance NA Product Enviro Compliance NA Product Enviro Compliance NA Product Enviro Compliance NA Product Envi-Stewards @ onsemi.com Product Enviro Compliance NA Product Enviro Compliance NA Product Envi-Stewards @ onsemi.com NA Nanufacturing Site Weight* UOM Un NRVTSAF360T3G 60V 3A Trench Rectifier in SMAFL package 2025-06-07 NA NRVTSAF360T3G 60V 3A Trench Rectifier in SMAFL package 2025-06-07 NA NRVTSAF360T3G 60V 3A Trench Rectifier in SMAFL package 2025-06-07 NA NRVTSAF360T3G 60V 3A Trench Rectifier in SMAFL package 2025-06-07 NA NRVTSAF360T3G NRVTSAF360T3G 60V 3A Trench Rectifier in SMAFL package 2025-06-07 NRVTSAF360T3G NRVTSAF360T3G NRVTSAF360T3G 60V 3A Trench Rectifier in SMAFL package 2025-06-07 NRVTSAF360T3G NRVTSAF360T3G NRVTSAF360T3G 60V 3A Trench Rectifier in SMAFL package 2025-06-07 NRVTSAF360T3G N	onsemi						I				2025-06-07			
Authorized Representative* Product-Env-Stewards Product Enviro Compliance Requester Item Number Mfr Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight* UOM University Manufacturing Process Information  Terminal Plating / Grid Array Material Terminal Base Alloy Terminal Base Alloy Terminal Plating / Grid Array Material Matte Tin (Sn) - annealed  CU Alloy  Title - Representative  Phone - Representative*  NA  Product-Env-Stewards@onsemi.com  Manufacturing Site Weight* UOM University Weight* UOM University Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles Seconds  Seconds  Seconds  Seconds  Seconds	Contact Name			Title - Contact			Phone - Contact*				Email - Contact*			
Product Envi-Stewards Requester Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight* UOM Uni NRVTSAF360T3G 60V 3A Trench Rectifier in SMAFL package 2025-06-07 MY1 83.64 mg Each Manufacturing Proccess Information  Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Matte Tin (Sn) - annealed CU Alloy 1 260 C 30 seconds 3	Product-Env-Stewards			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com			
Requester Item Number	Authorized Representative*			Title - Representative			Phone - Representative*			Email - Representative*				
NRVTSAF360T3G   60V 3A Trench Rectifier in SMAFL package   2025-06-07   MY1   83.64   mg   Each Matter Tin (Sn) - annealed   CU Alloy   1   260   C   30   seconds   3   Seconds   3   Seconds   S	Product-Env-Stewards			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com			
Manufacturing Proccess Information  Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles  Matte Tin (Sn) - annealed CU Alloy 1 260 C 30 seconds 3	Requester	Requester Item Number Mfr I		em Number Mfr Item Name			Effective D	ate Versi	ion	Manufacturing Site	W	eight*	UOM	Unit Type
Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles  Matte Tin (Sn) - annealed CU Alloy 1 260 C 30 seconds 3			NRVTSAF360T3G 60		60V 3A Trench Rectifier in SMAFL package		2025-06-07			MY1		.64	mg	Each
Matte Tin (Sn) - annealed CU Alloy 1 260 C 30 seconds 3 omments				arminal Paga	Alloy	STD 020 MSI Dating	Dook D	roass Pad	y Tamparati	May Time at Peak	Tomporotus	Numbo	r of Poflow Cyo	los
omments				-		STD-020 MSL Kanng							r of Reflow Cyc	ies
	•	i (Sii) - aimealed		U Alloy	1		200		<u> </u>	30	seconds	5 3		
ver 1 - maximum time at peak temperature during soldering is 10-50 seconds		me at neak temper-t	dunina a - 1-	doning is 10. 1	10 seconds									
or more information regarding material composition please refer to page 3														

RoHS Material Composition Declaration			Declaration Type *	Detailed							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its uppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier neter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 4 - Item(s	) does not contain RoHS restricted substance	es per the definition above except for selected exemp	otions Supplier Acceptance	* Accepted							
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.											
Supplier Digital Signature Ra	astislav Drska	-6_									

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Clip	7.0	mg	Supplier	Zinc (Zn)	7440-66-6		0.0084	mg
			Supplier	Iron (Fe)	7439-89-6		0.1645	mg
			Supplier	Copper (Cu)	7440-50-8		6.825	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0021	mg
Die	1.12	mg	Supplier	Silicon (Si)	7440-21-3		1.12	mg
Die Attach Solder	3.45	mg	Supplier	Silver (Ag)	7440-22-4		0.0862	mg
			A	Lead (Pb)	7439-92-1	7a	3.1913	mg
			Supplier	Tin (Sn)	7440-31-5		0.1725	mg
Lead Frame	28.84	mg	Supplier	Zinc (Zn)	7440-66-6		0.0346	mg
			Supplier	Iron (Fe)	7439-89-6		0.6777	mg
			Supplier	Copper (Cu)	7440-50-8		28.119	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0087	mg
Mold Compound-Black	41.85	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		4.185	mg
			Supplier	Carbon Black (C)	1333-86-4		0.2092	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		6.0682	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		27.2025	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		4.185	mg
Plating	1.38	mg	Supplier	Tin (Sn)	7440-31-5		1.38	mg