	© Copyright 2005. IP	Osition Dec C, Bannockb -American co	c laration ourn, Illinois. A opyright conve	All rights reserved u ntions.	nder both	This docume level parts, t	ent is a declarat he declaration	ion of the encompas	e substances sses all lowe	within the r er level mate	nanufacture rials for wh	er listed ite	em. Note: if anufacturer	the item is an as has engineering	ssembly with lowe responsibility.
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					ous Materia	als and Mfg Information				
Supplier	Information														
Company name* Compa				ompany unique ID			Unique ID Authority					Response Date*			
nsemi												2025-08-04			
Contact Na	ame		Title - Contact				Phone - Contact*					Email - Contact*			
Product-E	Env-Stewards		Product Enviro Compliance				NA					Product-Env-Stewards@onsemi.com			
uthorized	d Representative*		Title - Representative				Phone - Representative*				Email - Representative*				
Product-E	Env-Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
	Requester Item Number Mfr Iten		n Number Mfr Item Name				Effective Date	e Versi	on	Manufacturing Site		V	Veight*	UOM	Unit Type
		NTHL082N65S3F SUPERI		SUPERFET3 650	CRFET3 650V TO247		2025-08-04			СРА		5	456.925	mg	Each
/Ianufac	cturing Proccess Informat	ion										1			
	Terminal Plating / Grid Array Material		Ferminal Base Alloy J-STD-020 M		-STD-020 MS	L Rating	Peak Process Body Temperat		ure Max Time at Peak Temp		Temperatu	Ire Numb	er of Reflow Cyc	cles	
	Matte Tin (Sn) - annealed		CU Alloy NA			0 C		30		second	ls 3				
omments															
or more i	nformation regarding material of	composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		mium (Cr6+), Polybrominated Biphenyls (Pl		dmium and quantity limit of 0.1% by mass (10 minated Diphenyl Ethers (PBDE), and Bis(2-et					
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of				
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted				
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).						
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.									
Supplier Digital Signature	astislav Drska	Le							

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).										
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure		
Die	32.0	mg	Supplier	Silicon (Si)	7440-21-3		32	mg		
Die Attach Solder	35.025	mg	Supplier	Silver (Ag)	7440-22-4		0.8756	mg		
			А	Lead (Pb)	7439-92-1	7a	32.3981	mg		
			Supplier	Tin (Sn)	7440-31-5		1.7512	mg		
Lead Frame	3612.9	mg	Supplier	Iron (Fe)	7439-89-6		3.6129	mg		
			Supplier	Copper (Cu)	7440-50-8		3608.2031	mg		
			Supplier	Phosphorus (P)	7723-14-0		1.0839	mg		
Mold Compound-Black	1740.0	mg		Epoxy resin	proprietary data		200.1	mg		
			Supplier	Phenolic resins	Proprietary Data		147.9	mg		
			В	Antimony Trioxide (Sb2O3)	1309-64-4		43.5	mg		
			Supplier	Carbon Black (C)	1333-86-4		5.22	mg		
			Supplier	Fused Silica (SiO2)	60676-86-0		1343.2799	mg		
Plating	31.0	mg	Supplier	Tin (Sn)	7440-31-5		31	mg		
Wire Bond - Al	6.0	mg	Supplier	Aluminum (Al)	7429-90-5		6	mg		

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).