ABBOCIATION CONNECTING ELECTRONICS (NOUSTRIES®) International and Pan-American co	ourn, Illinois, All rights	s reserved under both	This docume level parts, th	ent is a declaration ne declaration end	n of the substanc compasses all lo	es within the manufactu wer level materials for v	arer listed ite which the ma	m. Note: if nufacturer l	the item is an as has engineering	sembly with lower responsibility.	
IPC Web Site for Information on I http://www.ipc.org/IPC-175x	21.1 IPC Web Site for Information on IPC-1752 Standard Form Typ			Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Information					on		
Supplier Information											
Company name*	apany name* Company unique ID			Unique ID Authority				Response Date*			
onsemi								2025-06-04			
Contact Name	Title - Contact		F	Phone - Contact*			Email - C	Email - Contact*			
Product-Env-Stewards	Product Enviro Comp	pliance	1	NA			Product-Env-Stewards@onsemi.com				
Authorized Representative*	Representative* Title - Representative			Phone - Representative*				Email - Representative*			
Product-Env-Stewards	pliance	ice N		NA			Product-Env-Stewards@onsemi.com				
Requester Item Number Mfr Item	n Number Mfr Ite	ber Mfr Item Name		Effective Date	Version	Manufacturing Site	W	'eight*	UOM	Unit Type	
NVMFS AFT3G	5C404NLWF T6 40V	V HEFET		2025-06-04		MY1)5.95	mg	Each	
Manufacturing Proccess Information											
Terminal Plating / Grid Array Material	Ferminal Base Alloy J-STD-020 MS		SL Rating	Peak Process Body Temperature Max Time at P		ture Max Time at Peal	k Temperature Number of Reflow Cycles				
Matte Tin (Sn) - annealed CU Alloy 1		1		260	С	30	second	s 3			
Comments											
level 1 - maximum time at peak temperature during so	Idering is 10-30 second	ds									
For more information regarding material composition	please refer to page 3	,									

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		mium (Cr6+), Polybrominated Biphenyls (Pl		dmium and quantity limit of 0.1% by mass (10 minated Diphenyl Ethers (PBDE), and Bis(2-et	
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).		
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required Requester) and click on Submit Form to h			e drop-dowi	a. This will display the signature area. Digita	lly sign the declaration (if required by the
Supplier Digital Signature	astislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).								
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Clip	4.8	mg	Supplier	Iron (Fe)	7439-89-6		0.0048	mg
			Supplier	Copper (Cu)	7440-50-8		4.7938	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0014	mg
Die	0.61	mg	Supplier	Silicon (Si)	7440-21-3		0.61	mg
Die Attach Solder	1.99	mg	Supplier	Silver (Ag)	7440-22-4		0.0498	mg
			А	Lead (Pb)	7439-92-1	7a	1.8407	mg
			Supplier	Tin (Sn)	7440-31-5		0.0995	mg
Lead Frame	47.6	mg	Supplier	Silver (Ag)	7440-22-4		0.0286	mg
			Supplier	Iron (Fe)	7439-89-6		0.0476	mg
			Supplier	Copper (Cu)	7440-50-8		47.5096	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0143	mg
Mold Compound-Black	49.2	mg		Epoxy resin	proprietary data		3.69	mg
			Supplier	Phenolic Resin	Proprietary Data		1.23	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		3.69	mg
			Supplier	Carbon Black (C)	1333-86-4		0.246	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		40.344	mg
Plating	1.7	mg	Supplier	Tin (Sn)	7440-31-5		1.7	mg
Wire Bond - Cu	0.05	mg	Supplier	Copper (Cu)	7440-50-8		0.05	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).