ABBOGIATION CONNECTING ELECTRONICS INDUSTRIES® INFORMATION AND ADDRESS INDUSTRIES®	IPC. Bannockl	ourn, Illinois, A	ll rights reserved untions.	under both	This docume level parts, t	ent is a declaration e	on of the su	ubstances s all lower	within the manufactu level materials for w	rer listed i which the r	tem. Note: nanufacture	if the item is an as er has engineering	sembly with lower responsibility.	
				Form Type Distribute					ials and Mfg Information					
Supplier Information														
Company name* Co			Company unique ID			Unique ID Authority					Response Date*			
onsemi											2025-06-04			
Contact Name Title - Contact			t			Phone - Contact*				Email -	Email - Contact*			
Product-Env-Stewards Product En			Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Authorized Representative* Title - Repr			presentative			Phone - Representative*				Email - Representative*				
Product-Env-Stewards Pr			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Requester Item Number	Mfr Item	n Number	Mfr Item Name			Effective Date	Version	Ν	Anufacturing Site		Weight*	UOM	Unit Type	
	SZMME	3Z27VALT1G ZEN SOT23 REG .2		G .225W SPCL		2025-06-04	CN1		N1	8.02		mg	Each	
Manufacturing Proccess Informa	ition							·						
Terminal Plating / Grid Array M	aterial	ial Terminal Base Alloy		J-STD-020 MSL Rating		Peak Process Body Temperatu		emperatur	ure Max Time at Peak Tempe		ture Num	ber of Reflow Cyc	les	
Matte Tin (Sn) - annealed CU Alle		CU Alloy	1			260 C		С	30 seco		seconds 3			
Comments														
evel 1 - maximum time at peak temperat	ure during so	ldering is 10-3	0 seconds											
or more information regarding material	composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Disobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted						
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all						
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	stislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.05	mg	Supplier	Silicon (Si)	7440-21-3		0.05	mg
Lead Frame	2.92	mg	В	Nickel (Ni)	7440-02-0		1.06	mg
			Supplier	Iron (Fe)	7439-89-6		1.4658	mg
			Supplier	Copper (Cu)	7440-50-8		0.3942	mg
Mold Compound-Black	4.9	mg	Supplier	Boron zinc hydroxide oxide	138265-88-0		0.147	mg
			Supplier	Zinc Monoxide (ZnO)	1314-13-2		0.0245	mg
			Supplier	2,4,6-triamino-s-triazincompd.withs- triazine-triol	37640-57-6		0.147	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		3.92	mg
			Supplier	Carbon Black (C)	1333-86-4		0.049	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		0.392	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.2205	mg
Plating	0.14	mg	Supplier	Tin (Sn)	7440-31-5		0.14	mg
Wire Bond - Cu	0.01	mg	Supplier	Copper (Cu)	7440-50-8		0.01	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted)