N-Channel Power MOSFET

24 V, 9 A, 16 mΩ, Dual ECH8

ECH8655R-R-TL-H



SOT−28FL / ECH8
CASE 318BF

Features

- Low ON−resistance
- 2.5 V Drive
- Common−drain Type
- Protection Diode in
- Built−in Gate Protection Resistor
- Best Suited for LiB Charging and Discharging Switch
- This Device is Pb−Free and are RoHS Compliant

Product & Package Information

- Package: ECH8
- JEITA, JEDEC: −
- Minimum Packing Quantity: 3,000 Pcs./Reel

Unit : mm (typ)
7011A−003

TopView

ECH8655R−R−TL−H



1 : Source1
2 : Gate1
3 : Source2
4 : Gate2
5 : Drain
6 : Drain
7 : Drain
8 : Drain

Bottom View

ECH8

Figure 1. Package Dimensions

GENERIC MARKING DIAGRAM



ELECTRICAL CONNECTION



PACKING TYPE: TL



ORDERING INFORMATION

See detailed ordering and shipping information on page 3 of this data sheet.

© Semiconductor Components Industries, LLC, 2013

SPECIFICATIONS

ABSOLUTE MAXIMUM RATINGS at T_A = 25°C

Parameter	Symbol	Conditions	Ratings	Unit
Drain−to−Source Voltage	V_{DSS}		24	V
Gate−to−Source Voltage	V_{GSS}		±12	V
Drain Current (DC)	I_D		9	A
Drain Current (Pulse)	I_{DP}	PW ≤ 10 μs, duty cycle ≤ 1%	60	A
Allowable Power Dissipation	P_D	When mounted on ceramic substrate (900 mm^2 × 0.8 mm) 1 unit	1.4	W
Total Dissipation	P_T	When mounted on ceramic substrate (900 mm^2 × 0.8 mm)	1.5	W
Channel Temperature	T_{ch}		150	°C
Storage Temperature	T_{stg}		−55 to +150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

ELECTRICAL CHARACTERISTICS at T_A = 25°C

Parameter	Symbol	Conditions	Ratings			Unit
			Min	Typ	Max	
Drain−to−Source Breakdown Voltage	$V_{(BR)DSS}$	I_D = 1 mA, V_{GS} = 0 V	24			V
Zero−Gate Voltage Drain Current	I_{DSS}	V_{DS} = 20 V, V_{GS} = 0V			1	μA
Gate−to−Source Leakage Current	I_{GSS}	V_{GS} = ±8 V, V_{DS} = 0 V			±10	μA
Cutoff Voltage	V_{GS}(off)	V_{DS} = 10 V, I_D = 1 mA	0.5		1.3	V
Forward Transfer Admittance	| yfs |	V_{DS} = 10 V, I_D = 4.5 A	4.8	8		S
Static Drain−to−Source On−State Resistance	R_{DS}(on)1	I_D = 4.5 A, V_{GS} = 4.5 V	10	13	16	mΩ
	R_{DS}(on)2	I_D = 4.5 A, V_{GS} = 4.0 V	10.5	13.5	16.5	mΩ
	R_{DS}(on)3	I_D = 4.5 A, V_{GS} = 3.1 V	11	15	20	mΩ
	R_{DS}(on)4	I_D = 2 A, V_{GS} = 2.5 V	13	18	24	mΩ
Turn−ON Delay Time	t_d(on)	See specified Test Circuit.		320		ns
Rise Time	t_r			1100		ns
Turn−OFF Delay Time	t_d(off)			2400		ns
Fall Time	t_f			2100		ns
Total Gate Charge	Qg	V_{DS} = 10 V, V_{GS} = 10 V, I_D = 9 A		16.8		nC
Gate−to−Source Charge	Qgs			1.6		nC
Gate−to−Drain “Miller” Charge	Qgd			4.8		nC
Diode Forward Voltage	V_{SD}	I_S = 9 A, V_{GS} = 0 V		0.8	1.2	V

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Share Feedback
Your Opinion Matters

Switching Time Test Circuit



Figure 2. Switching Time Test Circuit

ORDERING INFORMATION

Device	Package	Shipping†	Memo
ECH8655R−R−TL−H	ECH8	3,000 pcs./reel	Pb Free and Halogen Free

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS



Figure 3. $I_D - V_{DS}$



Figure 4. $I_D - V_{GS}$



Figure 5. $R_{DS(on)} - V_{GS}$



Figure 6. $R_{DS(on)} - T_A$



Figure 7. $|yfs| - I_D$



Figure 8. $I_S - V_{SD}$

Share Feedback
Your Opinion Matters



Figure 9. SW Time − I_D



Figure 10. V_{GS} − Q_g



Figure 11. ASO



Figure 12. P_D − T_A

Since the ECH8655R−R−TL−H is a MOSFET product, please avoid using this device in the vicinity of highly charged objects.

Share Feedback
Your Opinion Matters

SOT−28FL / ECH8
CASE 318BF
ISSUE O

DATE 31 MAR 2012



DOCUMENT NUMBER:	**98AON78700E**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**SOT−28FL / ECH8**		**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales