


NPN Silicon Transistor

KSC5027

High Voltage and High Reliability

- High Speed Switching
- Wide SOA



TO-220-3LD
CASE 340AT

ABSOLUTE MAXIMUM RATINGS (T_C = 25°C unless otherwise noted.)

Symbol	Parameter	Ratings	Unit
V _{CBO}	Collector-Base Voltage	1100	V
V _{CEO}	Collector-Emitter Voltage	800	V
V _{EBO}	Emitter-Base Voltage	7	V
I _C	Collector Current (DC)	3	A
I _{CP}	Collector Current (Pulse)	10	A
I _B	Base Current	1.5	A
P _C	Collector Dissipation (T _C = 25°C)	50	W
T _J	Junction Temperature	150	°C
T _{STG}	Storage Temperature	-55 ~ 150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

MARKING DIAGRAM



- &3 = Date Code (Year & Week)
- &K = Lot Run Traceability Code
- C5027 = Specific Device Code
- O = h_{FE} Grade

ORDERING INFORMATION

Device	Package	Shipping
KSC5027OTU	TO-220-3LD (Pb-Free, Halide Free)	1000 Units / Tube

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted.)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
BV _{CBO}	Collector-Base Breakdown Voltage	I _C = 1 mA, I _E = 0	1100	-	-	V
BV _{CEO}	Collector-Emitter Breakdown Voltage	I _C = 5 mA, I _B = 0	800	-	-	V
BV _{EBO}	Emitter-Base Breakdown Voltage	I _E = 1 mA, I _C = 0	7	-	-	V
V _{CES(sus)} 1	Collector-Emitter Sustaining Voltage	I _C = 1.5 A, I _{B1} = -I _{B2} = 0.3 A, L = 2 mH, Clamped	800	-	-	V
I _{CBO}	Collector Cut-off Current	V _{CB} = 800 V, I _E = 0	-	-	10	μA
I _{EBO}	Emitter Cut-off Current	V _{EB} = 5 V, I _C = 0	-	-	10	μA
h _{FE1} h _{FE2}	DC Current Gain	V _{CE} = 5 V, I _C = 0.2 A V _{CE} = 5 V, I _C = 1 A	10 8	-	40	
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C = 1.5 A, I _B = 0.3 A	-	-	2	V
V _{BE(sat)}	Base-Emitter Saturation Voltage	I _C = 1.5 A, I _B = 0.3 A	-	-	1.5	V
C _{ob}	Output Capacitance	V _{CB} = 10 V, I _E = 0, f = 1 MHz	-	60	-	μs
f _T	Current Gain Bandwidth Product	V _{CE} = 10 V, I _C = 0.2 A	-	15	-	MHz
t _{ON}	Turn On Time	V _{CC} = 400 V, I _C = 5 A, I _{B1} = -2.5, I _{B2} = 2 A, R _L = 200 Ω	-	-	0.5	μs
t _{STG}	Storage Time		-	-	3	μs
t _F	Fall Time		-	-	0.3	μs

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

h_{FE} Classification

Classification	N	R	O
H _{FE1}	10 ~ 20	15 ~ 30	20 ~ 40

TYPICAL CHARACTERISTICS




Figure 1. Static Characteristic




Figure 2. DC Current Gain




Figure 3. Base-Emitter Saturation Voltage
Collector-Emitter Saturation Voltage




Figure 4. Base-Emitter On Voltage




Figure 5. Switching Time






Figure 6. Safe Operating Area

TYPICAL CHARACTERISTICS (Continued)



V_{CE} , Collector-Emitter Voltage (V)

Figure 7. Reverse Bias Operating Areas




T_C , Case Temperature ($^{\circ}C$)

Figure 8. Power Derating

MECHANICAL CASE OUTLINE

PACKAGE DIMENSIONS


ON Semiconductor®



Scale 1:1

TO-220-3LD CASE 340AT ISSUE A

DATE 03 OCT 2017



DOCUMENT NUMBER:	98AON13818G	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	TO-220-3LD	PAGE 1 OF 1

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

onsemi, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales