NPN Silicon Power Darlington Transistors

MJE5740, MJE5742

The MJE5740 and MJE5742 Darlington transistors are designed for high−voltage power switching in inductive circuits.

Features

- These Devices are Pb−Free and are RoHS Compliant*

Applications

- Small Engine Ignition
- Switching Regulators
- Inverters
- Solenoid and Relay Drivers
- Motor Controls

POWER DARLINGTON TRANSISTORS
8 AMPERES
300−400 VOLTS
80 WATTS



TO−220AB
CASE 221A−09
STYLE 1





MAXIMUM RATINGS

Symbol	Rating	Value	Unit
$V_{CEO(sus)}$	Collector−Emitter Voltage MJE5740 MJE5742	 300 400	Vdc
V_{CEV}	Collector−Emitter Voltage MJE5740 MJE5742	 600 800	Vdc
V_{EB}	Emitter−Base Voltage	8	Vdc
I_C I_{CM}	Collector Current − Continuous − Peak (Note 1)	8 16	Adc
I_B I_{BM}	Base Current − Continuous − Peak (Note 1)	2.5 5	Adc
P_D	Total Device Dissipation @ T_A = 25°C Derate above 25°C	2 0.016	W W/°C
P_D	Total Device Dissipation @ T_C = 25°C Derate above 25°C	100 0.8	W W/°C
T_J, T_{stg}	Operating and Storage Junction Temperature Range	−65 to +150	°C

THERMAL CHARACTERISTICS

Symbol	Characteristics	Max	Unit
$R_{\theta JC}$	Thermal Resistance, Junction−to−Case	1.25	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction−to−Ambient	62.5	°C/W
T_L	Maximum Lead Temperature for Soldering Purposes 1/8″ from Case for 5 Seconds	275	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Pulse Test: Pulse Width = 5 ms, Duty Cycle ≤ 10%.

*For additional information on our Pb-Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

MARKING DIAGRAM



MJE574x	=	Device Code x = 0 or 2
G	=	Pb−Free Package
A	=	Assembly Location
Y	=	Year
WW	=	Work Week

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 6 of this data sheet.

NOTE: Some of the devices on this data sheet have been **DISCONTINUED**. Please refer to the table on page 6.

© Semiconductor Components Industries, LLC, 2015

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Symbol	Characteristic		Min	Typ	Max	Unit
OFF CHARACTERISTICS (Note 2)						
$V_{CEO(sus)}$	Collector−Emitter Sustaining Voltage (I_C = 50 mA, I_B = 0)	MJE5740 MJE5742	300 400	– –	– –	Vdc
I_{CEV}	Collector Cutoff Current (V_{CEV} = Rated Value, $V_{BE(off)}$ = 1.5 Vdc) (V_{CEV} = Rated Value, $V_{BE(off)}$ = 1.5 Vdc, T_C = 100°C)		– –	– –	1 5	mAdc
I_{EBO}	Emitter Cutoff Current (V_{EB} = 8 Vdc, I_C = 0)		–	–	75	mAdc
SECOND BREAKDOWN						
$I_{S/b}$	Second Breakdown Collector Current with Base Forward Biased		See Figure 6			
RBSOA	Clamped Inductive SOA with Base Reverse Biased		See Figure 7			
ON CHARACTERISTICS (Note 2)						
h_{FE}	DC Current Gain (I_C = 0.5 Adc, V_{CE} = 5 Vdc) (I_C = 4 Adc, V_{CE} = 5 Vdc)		50 200	100 400	– –	–
$V_{CE(sat)}$	Collector−Emitter Saturation Voltage (I_C = 4 Adc, I_B = 0.2 Adc) (I_C = 8 Adc, I_B = 0.4 Adc) (I_C = 4 Adc, I_B = 0.2 Adc, T_C = 100°C)		– – –	– – –	2 3 2.2	Vdc
$V_{BE(sat)}$	Base−Emitter Saturation Voltage (I_C = 4 Adc, I_B = 0.2 Adc) (I_C = 8 Adc, I_B = 0.4 Adc) (I_C = 4 Adc, I_B = 0.2 Adc, T_C = 100°C)		– – –	– – –	2.5 3.5 2.4	Vdc
V_f	Diode Forward Voltage (Note 3) (I_F = 5 Adc)		–	–	2.5	Vdc
SWITCHING CHARACTERISTICS						
Typical Resistive Load (Table 1)						
t_d	Delay Time	(V_{CC} = 250 Vdc, $I_{C(pk)}$ = 6 A I_{B1} = I_{B2} = 0.25 A, t_p = 25 μs, Duty Cycle ≤ 1%)	–	0.04	–	μs
t_r	Rise Time		–	0.5	–	μs
t_s	Storage Time		–	8	–	μs
t_f	Fall Time		–	2	–	μs
Inductive Load, Clamped (Table 1)						
t_{sv}	Voltage Storage Time	($I_{C(pk)}$ = 6 A, $V_{CE(pk)}$ = 250 Vdc I_{B1} = 0.06 A, $V_{BE(off)}$ = 5 Vdc)	–	4	–	μs
t_c	Crossover Time		–	2	–	μs

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

2. Pulse Test: Pulse Width 300 μs, Duty Cycle = 2%.
3. The internal Collector−to−Emitter diode can eliminate the need for an external diode to clamp inductive loads. Tests have shown that the Forward Recovery Voltage (V_f) of this diode is comparable to that of typical fast recovery rectifiers.

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS



Figure 1. Power Derating



Figure 2. Inductive Switching Measurements



Figure 3. DC Current Gain



Figure 4. Base−Emitter Voltage



Figure 5. Collector−Emitter Saturation Voltage

Share Feedback
Your Opinion Matters

Table 1. Test Conditions for Dynamic Performance

	REVERSE BIAS SAFE OPERATING AREA AND INDUCTIVE SWITCHING	RESISTIVE SWITCHING
TEST CIRCUITS		
CIRCUIT VALUES	COIL DATA: FERROXCUBE CORE #6656 FULL BOBBIN (~16 TURNS) #16 GAP FOR 200 μH/20 A L_{coil} = 200 μH V_{CC} = 30 V $V_{CE(pk)}$ = 250 Vdc $I_{C(pk)}$ = 6 A	V_{CC} = 250 V D1 = 1N5820 OR EQUIV.
TEST WAVEFORMS	OUTPUT WAVEFORMS  t_1 ADJUSTED TO OBTAIN I_C $t_1 \approx \frac{L_{coil}(I_{C_{pk}})}{V_{CC}}$ $t_2 \approx \frac{L_{coil}(I_{C_{pk}})}{V_{clamp}}$ TEST EQUIPMENT SCOPE-TEKTRONICS 475 OR EQUIVALENT	 t_r, t_f < 10 ns DUTY CYCLE = 1% R_B AND R_C ADJUSTED FOR DESIRED I_B AND I_C

Share Feedback
Your Opinion Matters

SAFE OPERATING AREA INFORMATION

FORWARD BIAS

There are two limitations on the power handling ability of a transistor: average junction temperature and second breakdown. Safe operating area curves indicate $I_C - V_{CE}$ limits of the transistor that must be observed for reliable operation; i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 6 is based on $T_C = 25°C$; $T_{J(pk)}$ is variable depending on power level. Second breakdown pulse limits are valid for duty cycles to 10% but must be derated when $T_C \geq 25°C$. Second breakdown limitations do not derate the same as thermal limitations. Allowable current at the voltages shown on Figure 6 may be found at any case temperature by using the appropriate curve on Figure 1.

REVERSE BIAS

For inductive loads, high voltage and high current must be sustained simultaneously during turn−off, in most cases, with the base to emitter junction reverse biased. Under these conditions the collector voltage must be held to a safe level at or below a specific value of collector current. This can be accomplished by several means such as active clamping, RC snubbing, load line shaping, etc. The safe level for these devices is specified as Reverse Bias Safe Operating Area and represents the voltage−current condition allowable during reverse biased turnoff. This rating is verified under clamped conditions so that the device is never subjected to an avalanche mode. Figure 7 gives the complete RBSOA characteristics.

The Safe Operating Area figures shown in Figures 6 and 7 are specified ratings for these devices under the test conditions shown.



Figure 6. Forward Bias Safe Operating Area



Figure 7. Reverse Bias Safe Operating Area

RESISTIVE SWITCHING PERFORMANCE



Figure 8. Turn−On Time



Figure 9. Turn−Off Time

Share Feedback
Your Opinion Matters

ORDERING INFORMATION

Device	Package	Shipping
MJE5742G	TO−220 (Pb−Free)	50 Units / Rail

DISCONTINUED (Note 4)

MJE5740G	TO−220 (Pb−Free)	50 Units / Rail

4. **DISCONTINUED:** This device is not recommended for new design. Please contact your **onsemi** representative for information. The most current information on this device may be available on www.onsemi.com.

Share Feedback
Your Opinion Matters



TO−220−3 10.10x15.12x4.45, 2.54P
CASE 221A
ISSUE AL

DATE 05 FEB 2025



MILLIMETERS			
DIM	MIN	NOM	MAX
A	4.07	4.45	4.83
A1	1.15	1.28	1.41
A2	2.04	2.42	2.79
b	1.15	1.34	1.52
b1	0.64	0.80	0.96
c	0.36	0.49	0.61
D	9.66	10.10	10.53
D1	8.43	8.63	8.83
E	14.48	15.12	15.75
E1	12.58	12.78	12.98
E2	1.27 REF		

MILLIMETERS			
DIM	MIN	NOM	MAX
e	2.42	2.54	2.66
e1	4.83	5.08	5.33
H1	5.97	6.22	6.47
L	12.70	13.49	14.27
L1	2.80	3.45	4.10
Q	2.54	2.79	3.04
øP	3.60	3.85	4.09
Z	−.−−	−.−−	3.48

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2018.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION Z DEFINES A ZONE WHERE ALL BODY AND LEAD IRREGULARITIES ARE ALLOWED.

STYLE 1:
PIN 1. BASE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

STYLE 2:
PIN 1. BASE
2. EMITTER
3. COLLECTOR
4. EMITTER

STYLE 3:
PIN 1. CATHODE
2. ANODE
3. GATE
4. ANODE

STYLE 4:
PIN 1. MAIN TERMINAL 1
2. MAIN TERMINAL 2
3. GATE
4. MAIN TERMINAL 2

STYLE 5:
PIN 1. GATE
2. DRAIN
3. SOURCE
4. DRAIN

STYLE 6:
PIN 1. ANODE
2. CATHODE
3. ANODE
4. CATHODE

STYLE 7:
PIN 1. CATHODE
2. ANODE
3. CATHODE
4. ANODE

STYLE 8:
PIN 1. CATHODE
2. ANODE
3. EXTERNAL TRIP/DELAY
4. ANODE

STYLE 9:
PIN 1. GATE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

STYLE 10:
PIN 1. GATE
2. SOURCE
3. DRAIN
4. SOURCE

STYLE 11:
PIN 1. DRAIN
2. SOURCE
3. GATE
4. SOURCE

STYLE 12:
PIN 1. MAIN TERMINAL 1
2. MAIN TERMINAL 2
3. GATE
4. NOT CONNECTED

DOCUMENT NUMBER:	**98ASB42148B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**TO−220−3 10.10x15.12x4.45, 2.54P**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales