MOSFET - Power, P-Channel, SOT-223

-10 A, -20 V

NTF6P02, NVF6P02

-10 AMPERES
-20 VOLTS
$R_{DS(on)}$ = 44 mΩ (Typ.)



P−Channel MOSFET

Features

- Low $R_{DS(on)}$
- Logic Level Gate Drive
- Diode Exhibits High Speed, Soft Recovery
- Avalanche Energy Specified
- NVF Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable*
- These Devices are Pb-Free and are RoHS Compliant

Typical Applications

- Power Management in Portables and Battery-Powered Products, i.e.: Cellular and Cordless Telephones and PCMCIA Cards

MARKING DIAGRAM & PIN ASSIGNMENT



SOT-223
CASE 318E
STYLE 3



A = Assembly Location
Y = Year
W = Work Week
F6P02 = Specific Device Code
▪ = Pb-Free Package

(Note: Microdot may be in either location)

MAXIMUM RATINGS (T_J = 25 °C unless otherwise noted)

Rating	Symbol	Value	Unit
Drain-to-Source Voltage	V_{DSS}	−20	Vdc
Gate-to-Source Voltage	V_{GS}	±8.0	Vdc
Drain Current (Note 1) – Continuous @ T_A = 25 °C – Continuous @ T_A = 70 °C – Single Pulse (t_p = 10 μs)	 I_D I_D I_{DM}	 −10 −8.4 −35	 Adc Apk
Total Power Dissipation @ T_A = 25 °C	P_D	8.3	W
Operating and Storage Temperature Range	T_J, T_{stg}	−55 to +150	°C
Single Pulse Drain-to-Source Avalanche Energy – Starting T_J = 25 °C (V_{DD} = −20 Vdc, V_{GS} = −5.0 Vdc, $I_{L(pk)}$ = −10 A, L = 3.0 mH, R_G = 25Ω)	E_{AS}	150	mJ
Thermal Resistance – Junction to Lead (Note 1) – Junction to Ambient (Note 2) – Junction to Ambient (Note 3)	 $R_{θJL}$ $R_{θJA}$ $R_{θJA}$	 15 71.4 160	°C/W
Maximum Lead Temperature for Soldering Purposes, 1/8″ from case for 10 seconds	T_L	260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Steady State.
2. When surface mounted to an FR4 board using 1” pad size, (Cu. Area 1.127 sq in), Steady State.
3. When surface mounted to an FR4 board using minimum recommended pad size, (Cu. Area 0.412 sq in), Steady State.

ORDERING INFORMATION

Device	Package	Shipping†
NTF6P02T3G	SOT-223 (Pb-Free)	4000 / Tape & Reel
NVF6P02T3G*	SOT-223 (Pb-Free)	4000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2013

ELECTRICAL CHARACTERISTICS (T_J = 25 °C unless otherwise noted)

Characteristic		Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Drain-to-Source Breakdown Voltage (Note 4) (V_{GS} = 0 Vdc, I_D = −250 μAdc) Temperature Coefficient (Positive)		$V_{(BR)DSS}$	 −20 −	 −25 −11	 − −	Vdc mV/°C
Zero Gate Voltage Drain Current (V_{DS} = −20 Vdc, V_{GS} = 0 Vdc) (V_{DS} = −20 Vdc, V_{GS} = 0 Vdc, T_J = 125 °C)		I_{DSS}	 − −	 − −	 −1.0 −10	μAdc
Gate-Body Leakage Current (V_{GS} = ±8.0 Vdc, V_{DS} = 0 Vdc)		I_{GSS}	−	−	±100	nAdc
ON CHARACTERISTICS (Note 4)						
Gate Threshold Voltage (Note 4) (V_{DS} = V_{GS}, I_D = −250 μAdc) Threshold Temperature Coefficient (Negative)		$V_{GS(th)}$	 −0.4 −	 −0.7 2.6	 −1.0 −	Vdc mV/°C
Static Drain-to-Source On-Resistance (Note 4) (V_{GS} = −4.5 Vdc, I_D = −6.0 Adc) (V_{GS} = −2.5 Vdc, I_D = −4.0 Adc) (V_{GS} = −2.5 Vdc, I_D = −3.0 Adc)		$R_{DS(on)}$	 − − −	 44 57 57	 50 70 −	mΩ
Forward Transconductance (Note 4) (V_{DS} = −10 Vdc, I_D = −6.0 Adc)		g_{fs}	−	12	−	Mhos
DYNAMIC CHARACTERISTICS						
Input Capacitance	(V_{DS} = −16 Vdc, V_{GS} = 0 V, f = 1.0 MHz)	C_{iss}	−	900	1200	pF
Output Capacitance		C_{oss}	−	350	500	
Transfer Capacitance		C_{rss}	−	90	150	
Input Capacitance	(V_{DS} = −10 Vdc, V_{GS} = 0 V, f = 1.0 MHz)	C_{iss}	−	940	−	pF
Output Capacitance		C_{oss}	−	410	−	
Transfer Capacitance		C_{rss}	−	110	−	
SWITCHING CHARACTERISTICS (Note 5)						
Turn-On Delay Time	(V_{DD} = −5.0 Vdc, I_D = −1.0 Adc, V_{GS} = −4.5 Vdc, R_G = 6.0 Ω)	$t_{d(on)}$	−	7.0	12	ns
Rise Time		t_r	−	25	45	
Turn-Off Delay Time		$t_{d(off)}$	−	75	125	
Fall Time		t_f	−	50	85	
Turn-On Delay Time	(V_{DD} = −16 Vdc, I_D = −6.0 Adc, V_{GS} = −4.5 Vdc, R_G = 2.5 Ω)	$t_{d(on)}$	−	8.0	−	ns
Rise Time		t_r	−	30	−	
Turn-Off Delay Time		$t_{d(off)}$	−	60	−	
Fall Time		t_f	−	60	−	
Gate Charge	(V_{DS} = −16 Vdc, I_D = −6.0 Adc, V_{GS} = −4.5 Vdc) (Note 4)	Q_T	−	15	20	nC
		Q_{gs}	−	1.7	−	
		Q_{gd}	−	6.0	−	
SOURCE-DRAIN DIODE CHARACTERISTICS						
Forward On-Voltage	(I_S = −3.0 Adc, V_{GS} = 0 Vdc) (Note 4) (I_S = −2.1 Adc, V_{GS} = 0 Vdc) (I_S = −3.0 Adc, V_{GS} = 0 Vdc, T_J = 125 °C)	V_{SD}	 − −	 −0.82 −0.74 −0.68	 −1.2 − −	Vdc

ELECTRICAL CHARACTERISTICS (T_J = 25 °C unless otherwise noted)

Characteristic		Symbol	Min	Typ	Max	Unit
SOURCE-DRAIN DIODE CHARACTERISTICS						
Reverse Recovery Time	(I_S = −3.0 Adc, V_{GS} = 0 Vdc, dI_S/dt = 100 A/μs) (Note 4)	t_{rr}	–	42	–	ns
		t_a	–	17	–	
		t_b	–	25	–	
Reverse Recovery Stored Charge		Q_{RR}	–	0.036	–	μC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

4. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.
5. Switching characteristics are independent of operating junction temperatures.

TYPICAL ELECTRICAL CHARACTERISTICS



Figure 1. On−Region Characteristics



Figure 2. Transfer Characteristics



Figure 3. On−Resistance versus Gate−to−Source Voltage



Figure 4. On−Resistance versus Drain Current and Gate Voltage



Figure 5. On−Resistance Variation with Temperature



Figure 6. Drain−to−Source Leakage Current versus Voltage

TYPICAL ELECTRICAL CHARACTERISTICS



Figure 7. Capacitance Variation



Figure 8. Gate−to−Source and Drain−to−Source Voltage versus Total Charge



Figure 9. Resistive Switching Time Variation versus Gate Resistance



Figure 10. Diode Forward Voltage versus Current

TYPICAL ELECTRICAL CHARACTERISTICS



Figure 11. FET Thermal Response

onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales