



SiC JFET Division

Is Now Part of



To learn more about onsemi™, please visit our website at
www.onsemi.com

onsemi and **onsemi** and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi** product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner. Other names and brands may be claimed as the property of others.

DATASHEET

UJ3D1220K2

Silicon Carbide (SiC) Diode - EliteSiC, TO-247-2L, 20 A, 1200 V SiC Merged PiN-Schottky (MPS) Diode


Rev. C, Jan 2025

Description

UnitedSiC offers the 3rd generation of high performance SiC Merged-PiN-Schottky (MPS) diodes. With zero reverse recovery charge and 175°C maximum junction temperature, these diodes are ideally suited for high frequency and high efficiency power systems with minimum cooling requirements.

Features

- ♦ Maximum operating temperature of 175°C
- ♦ Easy paralleling
- ♦ Extremely fast switching not dependent on temperature
- ♦ No reverse or forward recovery
- ♦ Enhanced surge current capability, MPS structure
- ♦ 100% UIS tested



Typical applications

- ♦ Power converters
- ♦ Industrial motor drives
- ♦ Switch mode power supplies
- ♦ Power factor correction modules

| Part Number | Package | Marking |
|-------------|-----------|------------|
| UJ3D1220K2 | TO-247-2L | UJ3D1220K2 |



Maximum Ratings

| Parameter | Symbol | Test Conditions | Value | Units |
|--|----------------|--|------------|----------------------|
| DC blocking voltage | V_R | | 1200 | V |
| Repetitive peak reverse voltage, $T_J=25^{\circ}\text{C}$ | V_{RRM} | | 1200 | V |
| Surge peak reverse voltage | V_{RSM} | | 1200 | V |
| Maximum DC forward current | I_F | $T_C = 135^{\circ}\text{C}$ | 20 | A |
| Non-repetitive forward surge current sine halfwave | I_{FSM} | $T_C = 25^{\circ}\text{C}, t_p = 10\text{ms}$ | 190 | A |
| | | $T_C = 110^{\circ}\text{C}, t_p = 10\text{ms}$ | 180 | |
| Repetitive forward surge current sine halfwave, $D=0.1$ | I_{FRM} | $T_C = 25^{\circ}\text{C}, t_p = 10\text{ms}$ | 71.9 | A |
| | | $T_C = 110^{\circ}\text{C}, t_p = 10\text{ms}$ | 40.9 | |
| Non-repetitive peak forward current | $I_{F,max}$ | $T_C = 25^{\circ}\text{C}, t_p = 10\mu\text{s}$ | 1300 | A |
| | | $T_C = 110^{\circ}\text{C}, t_p = 10\mu\text{s}$ | 1300 | |
| i^2t value | $\int i^2 dt$ | $T_C = 25^{\circ}\text{C}, t_p = 10\text{ms}$ | 181 | A^2s |
| | | $T_C = 110^{\circ}\text{C}, t_p = 10\text{ms}$ | 162 | |
| Power dissipation | P_{tot} | $T_C = 25^{\circ}\text{C}$ | 205 | W |
| | | $T_C = 135^{\circ}\text{C}$ | 55 | |
| Maximum junction temperature | $T_{J,max}$ | | 175 | $^{\circ}\text{C}$ |
| Operating and storage temperature | T_J, T_{STG} | | -55 to 175 | $^{\circ}\text{C}$ |
| Soldering temperatures, wavesoldering only allowed at leads | T_{sold} | 1.6mm from case for 10s | 260 | $^{\circ}\text{C}$ |

Thermal Characteristics

| Parameter | Symbol | Test Conditions | Value | | | Units |
|--------------------------------------|-----------------|-----------------|-------|------|------|----------------------|
| | | | Min | Typ | Max | |
| Thermal resistance, junction-to-case | $R_{\theta JC}$ | | | 0.56 | 0.73 | $^{\circ}\text{C/W}$ |

Electrical Characteristics ($T_J = +25^\circ\text{C}$ unless otherwise specified)

| Parameter | Symbol | Test Conditions | Value | | | Units |
|--|--------|---|-------|------|-----|---------------|
| | | | Min | Typ | Max | |
| Forward voltage | V_F | $I_F = 20\text{A}, T_J = 25^\circ\text{C}$ | - | 1.52 | 1.7 | V |
| | | $I_F = 20\text{A}, T_J = 150^\circ\text{C}$ | - | 2.15 | | |
| | | $I_F = 20\text{A}, T_J = 175^\circ\text{C}$ | - | 2.25 | | |
| Reverse current | I_R | $V_R = 1200\text{V}, T_J = 25^\circ\text{C}$ | - | 18 | 190 | μA |
| | | $V_R = 1200\text{V}, T_J = 175^\circ\text{C}$ | - | 500 | | |
| Total capacitive charge ⁽¹⁾ | Q_C | $V_R = 800\text{V}$ | | 83 | | nC |
| Total capacitance | C | $V_R = 1\text{V}, f = 1\text{MHz}$ | | 810 | | pF |
| | | $V_R = 400\text{V}, f = 1\text{MHz}$ | | 75 | | |
| | | $V_R = 800\text{V}, f = 1\text{MHz}$ | | 69 | | |
| Capacitance stored energy | E_C | $V_R = 800\text{V}$ | | 24.5 | | μJ |

(1) Q_C is independent on T_J , di_F/dt , and I_F as shown in the application note USCi_AN0011.

Typical Performance Diagrams




Figure 1. Typical forward characteristics




Figure 2. Typical forward characteristics in surge current




Figure 3. Typical reverse characteristics




Figure 4. Power dissipation




Figure 5. Diode forward current




Figure 6. Maximum transient thermal impedance




Figure 7. Capacitance vs. reverse voltage at 1MHz




Figure 8. Typical capacitive charge vs. reverse voltage




Figure 9. Typical capacitance stored energy vs. reverse voltage


Disclaimer

UnitedSiC reserves the right to change or modify any of the products and their inherent physical and technical specifications without prior notice. UnitedSiC assumes no responsibility or liability for any errors or inaccuracies within.

Information on all products and contained herein is intended for description only. No license, express or implied, to any intellectual property rights is granted within this document.

UnitedSiC assumes no liability whatsoever relating to the choice, selection or use of the UnitedSiC products and services described herein.

PACKAGE OUTLINE



| SYM | INCHES | | MILLIMETERS | |
|-----|-----------|-------|-------------|-------|
| | MIN | MAX | MIN | MAX |
| A | 0.185 | 0.209 | 4.70 | 5.31 |
| A1 | 0.087 | 0.102 | 2.21 | 2.61 |
| A2 | 0.059 | 0.098 | 1.50 | 2.49 |
| b | 0.039 | 0.055 | 0.99 | 1.40 |
| b2 | 0.065 | 0.094 | 1.65 | 2.39 |
| b4 | 0.102 | 0.135 | 2.59 | 3.43 |
| c | 0.015 | 0.035 | 0.38 | 0.89 |
| D | 0.819 | 0.845 | 20.80 | 21.46 |
| D1 | 0.515 | - | 13.08 | - |
| D2 | 0.02 | 0.053 | 0.51 | 1.35 |
| E | 0.610 | 0.640 | 15.49 | 16.26 |
| e | 0.214 BSC | | 5.44 BSC | |
| E1 | 0.530 | - | 13.46 | - |
| E2 | 0.135 | 0.157 | 3.43 | 3.99 |
| L | 0.780 | 0.800 | 19.81 | 20.32 |
| L1 | - | 0.177 | - | 4.50 |
| ØP | 0.140 | 0.144 | 3.56 | 3.66 |
| ØP1 | 0.278 | 0.291 | 7.06 | 7.39 |
| Q | 0.212 | 0.244 | 5.39 | 6.20 |
| S | 0.243 BSC | | 6.17 BSC | |
| W | - | 0.006 | - | 0.15 |

PART MARKING**PART NUMBER** **USiC**
XYYYWW LLL

PART NUMBER = REFER TO
DS_PN DECODER FOR DETAILS

X = ASSEMBLY SITE

YY = YEAR

WW = WORK WEEK

LLL = LOT ID

PACKING TYPE

ANTI-STATIC TUBE

QUANTITY /TUBE : 30 UNITS

DISCLAIMER

United Silicon Carbide, Inc. reserves the right to change or modify any of the products and their inherent physical and technical specifications without prior notice. United Silicon Carbide, Inc. assumes no responsibility or liability for any errors or inaccuracies within.

Information on all products and contained herein is intended for description only. No license, express or implied, to any intellectual property rights is granted within this document.

United Silicon Carbide, Inc. assumes no liability whatsoever relating to the choice, selection or use of the United Silicon Carbide, Inc. products and services described herein.

onsemi, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales