

NCV760040 Evaluation Kit User's Manual

EVBUM2930/D

Features

This document describes NCV760040 evaluation kit for the NCV760040 Quad High-side driver. The kit consists of the NCV760040 evaluation board, ONMCU3V3R2GEVB control board and an USB-C cable. The evaluation board contains all the application components allowing evaluation of NCV760040 functionality and its major parameters.

Evaluation Board Features

- On-board 3.3 V LDO
- Two Supply Inputs
- Device I²C Address Selection
- Two Current Limit and Current Sense Configurability
- LEDs For Output Status Indication and FAULT Diagnostics
- Good Thermal Connection of NCV760040 Allowing High Current Capability
- Oscilloscope Test-Points on All Important Signals
- Compatible with [ONMCU3V3R2GEVB](#), [ONMCU3V3R1GEVB](#) (3.3 V) or [ONMCU5V0R2GEVB](#), [ONMCU5V0R1GEVB](#) (5.0 V) MCU Module with USB Interface for PC Control
- Easy-to-Use GUI
- Header Providing Stacking of the Evaluation Boards and Connection of the Board Into a More Complex Application Setup




Figure 1. Board Picture


EVBUM2930/D

Figure 2. NCV760040 Evaluation Board Schematic

ABSOLUTE MAXIMUM RATINGS

Rating	External Pin	Min	Max	Unit
Power Supply voltage 1	Vbat	−40	40	V
Power Supply voltage 2	VIN1	−0.3	40	V
Outputs voltage	OUT1, OUT2, OUT3, OUT4	−0.3	40	V
Outputs current	OUT1, OUT2, OUT3, OUT4	0	Internally limited	A
Digital inputs / outputs voltage	EN, SCL, SDA, FAULT, Range2	−0.3	5.5	V
SDA output current	SDA	−10	20	mA
NCV760040 junction temperature	−	−40	+150	°C
Board temperature	−	−40	+125	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

RECOMMENDED OPERATING RANGES

Rating	External Pin	Min	Max	Unit
Power Supply voltage 1	Vbat	4.5	28	V
Power Supply voltage 2	VIN1	4.5	28	V
Digital inputs / outputs voltage	EN, SCL, SDA, FAULT, Range2	0	3.3	V
Outputs current	OUT1, OUT2, OUT3, OUT4 – Single Channel On, $T_J < 150^{\circ}\text{C}$ – All Channels On, $T_A < 125^{\circ}\text{C}$ – All Channels On, $T_A < 105^{\circ}\text{C}$ – All Channels On, $T_A < 85^{\circ}\text{C}$	– – – –	1.2 529 710 854	A
I ² C frequency	SCL, SDA	–	1.0	MHz
NCV760040 junction temperature	–	–40	+150	$^{\circ}\text{C}$
Board temperature	–	–40	+105	$^{\circ}\text{C}$

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

FUNCTIONAL DESCRIPTION

The NCV760040 is an I²C-enabled target device featuring four independent high-side outputs constructed using two back-to-back NMOS power transistors for true reverse current blocking capability. Each output is protected against short to battery, short to ground, and overtemperature faults. An off-state open load diagnostic supports system-level fault detection.

Supply strategy

The supply is divided into three main paths:

- Main (battery) supply – this path supplies VIN2 of NCV760040 as well as on-board 3.3 V LDO for VDD logic supply of NCV760040. This path is protected against reverse polarity voltage.
- VIN1 supply – this path is directly connected to VIN1 pin of NCV760040 and therefore cannot withstand reverse polarity. It may be connected to VIN2 through a jumper J_VIN.
- The MCU is supplied from USB to maintain USB connection with the MCU as well as to allow quiescent current measurement of NCV760040.

As the ONMCU board is supplied from the USB connector, allowing quiescent current measurement of NCV760040. To measure the VDD consumption of NCV760040 only, 0R resistor Rvdd has to be replaced by 10-100R resistor.

Getting Started

The board supports a full access to NCV760040 control and diagnostics using a PC connected to the board via USB and ONMCU daughterboard.

The GUI software is part of the installation package, which can be downloaded from the EVK product page: [onsemi EVK Product Page](#).

On top of that, an external I²C master might control NCV760040 through IO connector with the ONMCU daughterboard present (but not communicating) or removed.

Device I²C Address

To allow I²C communication, a valid address has to be selected through the ADD header array, connecting appropriate resistors to the ADD pin. The device is able to detect invalid address (no jumper or jumper inappropriately placed). The same address has to be selected in the software.




Figure 3. EVB Address Setting (Target Address 0)

Current Limit

The device contains a current limit for the outputs. It is defined by Rcl1/2 resistors. By default, a limit of 0.6 A is selected. It might be changed to 0.3 A by pulling Range1 signal low. On top of that, the device allows increasing the limit through the I²C control up to the double.

Current Sensing

The device provides possibility to sense the selected output current. The current sense range is defined by Rcs1/2 resistors. By default, the range of 1.2 A is selected to cover the highest possible current limit range. The range selection is bound with the current limit selection, controlled by the Range1 signal. The software is able to display the internal ADC readback value as well as its current representation and voltage over Rcs measured directly by the MCU. The maximum sensed current is limited to 600 mA due to 3.3 V VDD supply.

Functions of LEDs

The board contains LEDs indicating status of the outputs. LED1-4 indicate active output, including diagnostic current. Due to a higher voltage drop they do not affect the open load diagnostic feature.

LED_FLT indicate a fault if enabled in the Fault Pin Configuration register (0x81).

Table 1. Functions of LEDs

LED	Function	Color
LED1	OUT1 Status	Blue
LED2	OUT2 Status	Blue
LED3	OUT3 Status	Blue
LED4	OUT4 Status	Blue
LED_FLT	FLT pin Fault indication	Red

Stacking the Boards

More “slave” evaluation boards without ONMCU may be stacked using IOa and IOb connectors. Each board must have unique I²C address (ADD jumpers) and VIN1/2 supply connected.

To control the current limit and current sense range of the “slave” boards from the software, pins 11 and 12 on the ONMCU socket have to be bridged on the “slave” boards.

Control Software

The software provides full access to all the device I²C registers, EN and FAULT pins and allows changing the current sense and limit ranges.

The connection is done through a “Connect” button in the main framework, as shown in Figure 3. If the board is not detected automatically (COM port appears), click the Refresh button. After successful connection, the I²C interface is configured automatically and EN pin set high. Disconnection of the board is detected automatically. The “mockup” is a software standalone mode without the board connected. All the returned values are random, nothing is sent to a virtual COM port.

The software provides calculation of the ADC readout to the current in line with the Range (Rcs1/2 resistors) selection. In addition, the voltage over the Rcs1/2 resistors is sampled by the MCU ADC converter with the accuracy of 10%.

Firmware Updates

The ONMCU board and PC software supports firmware updates through the USB. The update procedure is described in a separate document. The update is normally not necessary, the boards are delivered with programmed MCU.



Figure 4. NCV760040 Controller Framework

EVBUM2930/D

Q4 (Ctrl+1) Device

I2C Configuration and Device Control

I2C Address: ☐ FAULT ☒ EN_PIN ☒ RNG1 ☒ RNG2 Device ID:

OUTPUT CONTROL (0x11)

☐ EN_OUT_1 ☐ EN_OUT_2 ☐ EN_OUT_3 ☒ EN_OUT_4
☐ RB_BLK_1 ☐ RB_BLK_2 ☐ RB_BLK_3 ☐ RB_BLK_4

DIAGNOSTICS OUT 1 (0x31)

☐ STATUS_OUT1 ☐ OL_OUT1 ☐ TW_OUT1
☐ STB_OUT1 ☐ ILIM_OUT1 ☐ TSD_OUT1

CONFIGURATION (0x12)

☐ LATCH_1 ☐ LATCH_2 ☐ LATCH_3 ☐ LATCH_4
☐ OVLO

SENSE_SELECT [2:0]:

DIAGNOSTICS OUT 2 (0x41)

☐ STATUS_OUT2 ☐ OL_OUT2 ☐ TW_OUT2
☐ STB_OUT2 ☐ ILIM_OUT2 ☐ TSD_OUT2

CONFIGURATION 2 (0xA2)

OL_EN_X [2:0]:

☐ COR

DIAGNOSTICS OUT 3 (0x51)

☐ STATUS_OUT3 ☐ OL_OUT3 ☐ TW_OUT3
☐ STB_OUT3 ☐ ILIM_OUT3 ☐ TSD_OUT3

CURRENT LIMIT SHIFT (0xA1)

CL_SHIFT_1 [1:0]:

CL_SHIFT_2 [1:0]:

CL_SHIFT_3 [1:0]:

CL_SHIFT_4 [1:0]:

DIAGNOSTICS OUT 4 (0x61)

☐ STATUS_OUT4 ☐ OL_OUT4 ☐ TW_OUT4
☐ STB_OUT4 ☐ ILIM_OUT4 ☐ TSD_OUT4

FAULT PIN CONFIGURATION (0x81)

☐ OV_UV ☐ STB_ALL ☐ OL_ALL ☐ ILIM_ALL ☐ TSD_ALL

ADC READOUT (0x21)

SENSE [7:0]: 0.189A MCU: 0.177A

GLOBAL DIAGNOSTICS (0x71)

☐ VIN1_OV ☐ VIN1_UV ☐ VIN2_OV ☐ VIN2_UV
☐ GL_FAULT

ADC READOUT (0x21)

SENSE [7:0]: 0.189A MCU: 0.177A

GLOBAL DIAGNOSTICS (0x71)

☐ VIN1_OV ☐ VIN1_UV ☐ VIN2_OV ☐ VIN2_UV
☐ GL_FAULT

ADC READOUT (0x21)

SENSE [7:0]: 0.189A MCU: 0.177A

GLOBAL DIAGNOSTICS (0x71)

☐ VIN1_OV ☐ VIN1_UV ☐ VIN2_OV ☐ VIN2_UV
☐ GL_FAULT

ADC READOUT (0x21)

SENSE [7:0]: 0.189A MCU: 0.177A

GLOBAL DIAGNOSTICS (0x71)

☐ VIN1_OV ☐ VIN1_UV ☐ VIN2_OV ☐ VIN2_UV
☐ GL_FAULT

ADC READOUT (0x21)

SENSE [7:0]: 0.189A MCU: 0.177A

GLOBAL DIAGNOSTICS (0x71)

☐ VIN1_OV ☐ VIN1_UV ☐ VIN2_OV ☐ VIN2_UV
☐ GL_FAULT

ADC READOUT (0x21)

SENSE [7:0]: 0.189A MCU: 0.177A

GLOBAL DIAGNOSTICS (0x71)

☐ VIN1_OV ☐ VIN1_UV ☐ VIN2_OV ☐ VIN2_UV
☐ GL_FAULT

ADC READOUT (0x21)

SENSE [7:0]: 0.189A MCU: 0.177A

GLOBAL DIAGNOSTICS (0x71)

☐ VIN1_OV ☐ VIN1_UV ☐ VIN2_OV ☐ VIN2_UV
☐ GL_FAULT

ADC READOUT (0x21)

SENSE [7:0]: 0.189A MCU: 0.177A

GLOBAL DIAGNOSTICS (0x71)

☐ VIN1_OV ☐ VIN1_UV ☐ VIN2_OV ☐ VIN2_UV
☐ GL_FAULT

ADC READOUT (0x21)

SENSE [7:0]: 0.189A MCU: 0.177A

GLOBAL DIAGNOSTICS (0x71)

☐ VIN1_OV ☐ VIN1_UV ☐ VIN2_OV ☐ VIN2_UV
☐ GL_FAULT

ADC READOUT (0x21)

SENSE [7:0]: 0.189A MCU: 0.177A

GLOBAL DIAGNOSTICS (0x71)

☐ VIN1_OV ☐ VIN1_UV ☐ VIN2_OV ☐ VIN2_UV
☐ GL_FAULT

ADC READOUT (0x21)

SENSE [7:0]: 0.189A MCU: 0.177A

GLOBAL DIAGNOSTICS (0x71)

☐ VIN1_OV ☐ VIN1_UV ☐ VIN2_OV ☐ VIN2_UV
☐ GL_FAULT

ADC READOUT (0x21)

SENSE [7:0]: 0.18

Figure 5. NCV760040 Control Window

PCB DRAWINGS

Assebmly Drawings




Figure 6. NCV760040 EVB PCB Top Assembly Drawing




Figure 7. NCV760040 EVB PCB Bottom Assembly Drawing (Bottom View)

Composite Drawings




Figure 8. NCV760040 EVB PCB Top Composite Drawing




Figure 9. NCV760040 EVB PCB Bottom Composite Drawing (Bottom View)




Figure 10. NCV760040 EVB PCB Internal Plane 1 Drawing




Figure 11. NCV760040 EVB PCB Internal Plane 2 Drawing

EVBUM2930/D

REVISION HISTORY

Revision	Description of Changes	Date
0	Eval Board User's Manual creation.	6/20/2025

onsemi is licensed by the Philips Corporation to carry the I²C bus protocol.

onsemi, **onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

The evaluation board/kit (research and development board/kit) (hereinafter the "board") is not a finished product and is not available for sale to consumers. The board is only intended for research, development, demonstration and evaluation purposes and will only be used in laboratory/development areas by persons with an engineering/technical training and familiar with the risks associated with handling electrical/mechanical components, systems and subsystems. This person assumes full responsibility/liability for proper and safe handling. Any other use, resale or redistribution for any other purpose is strictly prohibited.

THE BOARD IS PROVIDED BY ONSEMI TO YOU "AS IS" AND WITHOUT ANY REPRESENTATIONS OR WARRANTIES WHATSOEVER. WITHOUT LIMITING THE FOREGOING, ONSEMI (AND ITS LICENSORS/SUPPLIERS) HEREBY DISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES IN RELATION TO THE BOARD, ANY MODIFICATIONS, OR THIS AGREEMENT, WHETHER EXPRESS, IMPLIED, STATUTORY OR OTHERWISE, INCLUDING WITHOUT LIMITATION ANY AND ALL REPRESENTATIONS AND WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE, NON-INFRINGEMENT, AND THOSE ARISING FROM A COURSE OF DEALING, TRADE USAGE, TRADE CUSTOM OR TRADE PRACTICE.

onsemi reserves the right to make changes without further notice to any board.

You are responsible for determining whether the board will be suitable for your intended use or application or will achieve your intended results. Prior to using or distributing any systems that have been evaluated, designed or tested using the board, you agree to test and validate your design to confirm the functionality for your application. Any technical, applications or design information or advice, quality characterization, reliability data or other services provided by **onsemi** shall not constitute any representation or warranty by **onsemi**, and no additional obligations or liabilities shall arise from **onsemi** having provided such information or services.

onsemi products including the boards are not designed, intended, or authorized for use in life support systems, or any FDA Class 3 medical devices or medical devices with a similar or equivalent classification in a foreign jurisdiction, or any devices intended for implantation in the human body. You agree to indemnify, defend and hold harmless **onsemi**, its directors, officers, employees, representatives, agents, subsidiaries, affiliates, distributors, and assigns, against any and all liabilities, losses, costs, damages, judgments, and expenses, arising out of any claim, demand, investigation, lawsuit, regulatory action or cause of action arising out of or associated with any unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of any products and/or the board.

This evaluation board/kit does not fall within the scope of the European Union directives regarding electromagnetic compatibility, restricted substances (RoHS), recycling (WEEE), FCC, CE or UL, and may not meet the technical requirements of these or other related directives.

FCC WARNING – This evaluation board/kit is intended for use for engineering development, demonstration, or evaluation purposes only and is not considered by **onsemi** to be a finished end product fit for general consumer use. It may generate, use, or radiate radio frequency energy and has not been tested for compliance with the limits of computing devices pursuant to part 15 of FCC rules, which are designed to provide reasonable protection against radio frequency interference. Operation of this equipment may cause interference with radio communications, in which case the user shall be responsible, at its expense, to take whatever measures may be required to correct this interference.

onsemi does not convey any license under its patent rights nor the rights of others.

LIMITATIONS OF LIABILITY: **onsemi** shall not be liable for any special, consequential, incidental, indirect or punitive damages, including, but not limited to the costs of requalification, delay, loss of profits or goodwill, arising out of or in connection with the board, even if **onsemi** is advised of the possibility of such damages. In no event shall **onsemi**'s aggregate liability from any obligation arising out of or in connection with the board, under any theory of liability, exceed the purchase price paid for the board, if any.

The board is provided to you subject to the license and other terms per **onsemi**'s standard terms and conditions of sale. For more information and documentation, please visit www.onsemi.com.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales